

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12717137

Frame	: 182/4TC	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 37.8 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.0080 kgm ²
Design	: B		

Output [HP]	3	2	2	2	3	3	3
Poles	2	2	2	2	2	2	2
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	7.52/3.76	3.28	3.24	3.24	4.44	4.32	4.26
L. R. Amperes [A]	64.7/32.3	31.8	35.0	36.0	31.1	32.8	35.4
LRC [A]	8.6x(Code K)	9.7x(Code M)	10.8x(Code N)	11.1x(Code P)	7.0x(Code H)	7.6x(Code J)	8.3x(Code K)
No load current [A]	3.20/1.60	1.50	1.65	1.80	1.50	1.70	1.80
Rated speed [RPM]	3515	2935	2940	2945	2890	2900	2910
Slip [%]	2.36	2.17	2.00	1.83	3.67	3.33	3.00
Rated torque [kgfm]	0.619	0.495	0.494	0.493	0.753	0.751	0.748
Locked rotor torque [%]	250	280	320	350	190	210	229
Breakdown torque [%]	380	420	470	509	270	300	330
Service factor	1.25	1.25	1.25	1.25	1.25	1.25	1.25
Temperature rise	80 K	80 K	80 K	80 K	80 K	80 K	80 K
Locked rotor time	46s (cold) 26s (hot)	52s (cold) 29s (hot)	43s (cold) 24s (hot)	48s (cold) 27s (hot)	41s (cold) 23s (hot)	43s (cold) 24s (hot)	34s (cold) 19s (hot)
Noise level ²	66.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)
Efficiency (%)	25%						
	50%	82.0	81.0	80.6	79.7	84.0	84.0
	75%	86.0	84.5	84.5	84.1	85.5	85.5
	100%	86.5	85.8	85.8	85.9	85.5	85.5
Power Factor	25%						
	50%	0.70	0.63	0.58	0.55	0.76	0.71
	75%	0.80	0.75	0.71	0.67	0.84	0.81
	100%	0.85	0.81	0.78	0.75	0.88	0.86

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	14.6	14.6	14.6	14.6	14.6	14.6
	P2 (0,5;1,0)	10.7	10.7	10.7	10.7	10.7	10.7
	P3 (0,25;1,0)	9.4	9.4	9.4	9.4	9.4	9.4
	P4 (0,9;0,5)	8.3	8.3	8.3	8.3	8.3	8.3
	P5 (0,5;0,5)	4.5	4.5	4.5	4.5	4.5	4.5
	P6 (0,5;0,25)	3.1	3.1	3.1	3.1	3.1	3.1
	P7 (0,25;0,25)	1.8	1.8	1.8	1.8	1.8	1.8

Bearing type	: Drive end 6207 ZZ Non drive end 6206 ZZ	Foundation loads	
Sealing	: V'Ring V'Ring	Max. traction	: 32 kgf
Lubrication interval	: - -	Max. compression	: 70 kgf
Lubricant amount	: - -		
Lubricant type	: Mobil Polyrex EM		

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	13/07/2025		Page 1 / 9	Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes
USABLE @208V 8.01A SF 1.15 SFA 9.21A

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 9		Revision
Checked by					
Date	13/07/2025				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12717137



Performance : 230/460 V 60 Hz 2P

Rated current : 7.52/3.76 A
LRC : 8.6
Rated torque : 0.619 kgfm
Locked rotor torque : 250 %
Breakdown torque : 380 %
Rated speed : 3515 rpm

Moment of inertia (J) : 0.0080 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by					
Date					
	13/07/2025			3 / 9	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12717137



Performance : 380 V 50 Hz 2P IE3

Rated current : 3.28 A
LRC : 9.7
Rated torque : 0.495 kgfm
Locked rotor torque : 280 %
Breakdown torque : 420 %
Rated speed : 2935 rpm

Moment of inertia (J) : 0.0080 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 4 / 9	Revision
Checked by					
Date	13/07/2025				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12717137



Performance : 400 V 50 Hz 2P IE3

Rated current : 3.24 A
LRC : 10.8
Rated torque : 0.494 kgfm
Locked rotor torque : 320 %
Breakdown torque : 470 %
Rated speed : 2940 rpm

Moment of inertia (J) : 0.0080 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 5 / 9	Revision
Checked by					
Date	13/07/2025				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12717137



Performance : 415 V 50 Hz 2P IE3

Rated current : 3.24 A
LRC : 11.1
Rated torque : 0.493 kgfm
Locked rotor torque : 350 %
Breakdown torque : 509 %
Rated speed : 2945 rpm

Moment of inertia (J) : 0.0080 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				6 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12717137



Performance : 380 V 50 Hz 2P IE2

Rated current : 4.44 A
LRC : 7.0
Rated torque : 0.753 kgfm
Locked rotor torque : 190 %
Breakdown torque : 270 %
Rated speed : 2890 rpm

Moment of inertia (J) : 0.0080 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 7 / 9	Revision
Checked by					
Date	13/07/2025				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12717137



Performance : 400 V 50 Hz 2P IE2

Rated current : 4.32 A
LRC : 7.6
Rated torque : 0.751 kgfm
Locked rotor torque : 210 %
Breakdown torque : 300 %
Rated speed : 2900 rpm

Moment of inertia (J) : 0.0080 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 8 / 9	Revision
Checked by					
Date	13/07/2025				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12717137



Performance : 415 V 50 Hz 2P IE2

Rated current : 4.26 A
LRC : 8.3
Rated torque : 0.748 kgfm
Locked rotor torque : 229 %
Breakdown torque : 330 %
Rated speed : 2910 rpm

Moment of inertia (J) : 0.0080 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 9 / 9Revision			
Checked by					
Date	13/07/2025				