

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : General High Efficiency Three-Phase Product code : 11993756

Frame	: E143/5TC	Locked rotor time	: 27s (cold) 15s (hot)
Output	: 1 HP (0.75 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 1.20 A	Protection degree	: IP21
L. R. Amperes	: 9.36 A	Cooling method	: IC01 - ODP
LRC	: 7.8x(Code L)	Mounting	: F-1
No load current	: 0.800 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1740 rpm	Noise level ²	: 50.0 dB(A)
Slip	: 3.33 %	Starting method	: Direct On Line
Rated torque	: 0.417 kgfm	Approx. weight ³	: 20.9 kg
Locked rotor torque	: 310 %		
Breakdown torque	: 350 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0053 kgm ²		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	80.0	81.5	82.5	Max. traction	: 31 kgf
Power Factor	0.57	0.68	0.76	Max. compression	: 52 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6205 ZZ	6204 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	14/07/2025			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : General High Efficiency Three-Phase

Product code : 11993756



Performance : 575 V 60 Hz 4P

Rated current : 1.20 A
LRC : 7.8
Rated torque : 0.417 kgfm
Locked rotor torque : 310 %
Breakdown torque : 350 %
Rated speed : 1740 rpm

Moment of inertia (J) : 0.0053 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date					