

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12678202
Catalog # :

Frame	: 182/4TCZ	Locked rotor time	: 55s (cold) 31s (hot)
Output	: 5 HP (3.7 kW)	Temperature rise	: 105 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 14.2/7.11 A	Protection degree	: IP55
L. R. Amperes	: 135/67.5 A	Cooling method	: IC410 - TENV
LRC	: 9.5x(Code M)	Mounting	: F-1
No load current	: 8.60/4.30 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1765 rpm	Starting method	: VFD
Slip	: 1.94 %	Approx. weight ³	: 110 lb
Rated torque	: 14.9 ft.lb		
Locked rotor torque	: 290 %		
Breakdown torque	: 450 %		
Insulation class	: H		
Service factor	: 1.00		
Moment of inertia (J)	: 0.4627 sq.ft.lb		
Design	: A		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	0.000	87.5	89.5	89.5	Max. traction	: 373 lb
Power Factor	0.00	0.51	0.64	0.73	Max. compression	: 483 lb

		Drive end	Non drive end
Bearing type	:	6207 ZZ C3	6207 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	0 h	0 h
Lubricant amount	:	0 g	0 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	06/03/2025			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2Revision	
Checked by					
Date	06/03/2025				