

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : Special Motor

Frame	: 56CZ	Locked rotor time	: 19 s (hot) 34 s (cold)
Output	: 1 HP (0.75 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 575 V	Altitude	: 3280 ft
Rated current	: 1.18 A	Protection degree	: IP55
L. R. Amperes	: 10.1 A	Cooling method	: IC410 - TENV
LRC	: 8.6 Code M	Mounting	: F-1/B34R(D)
No load current	: 0.712 A	Rotation ¹	: Both
Rated speed	: 1765 rpm	Noise level ²	: -
Slip	: 1.94 %	Vibration class	: A
Rated torque	: 2.97 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 280.0 %	Approx. weight ³	: 38.5 lb
Pull up torque	: 235.0 %	Painting plan	: 207N
Breakdown torque	: 300.0 %	Color	: MUNSELL N 1 - MATTE
Insulation class	: H	Design	: B
Service factor	: 1.00		
Moment of inertia (J)	: 0.1305 sq.ft.lb		

Output	50%	75%	100%	Load type	: -
Efficiency (%)	82.5	84.0	85.5	Load torque	: -
Power Factor	0.52	0.66	0.75	Load inertia (J=GD ² /4)	: -
Bearing type	Drive end 6204-ZZ	Non drive end 6203-ZZ		Foundation loads	
Lubrication interval	-	-		Max. traction	:
Lubricant amount	-	-		Max. compression	:
Lubricant type	MOBIL POLYREX EM				

Notes

See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Rev.	Checked	Date	
Performed by	martint				Page 1 / 2	Rev. 0
Checked by						
Date	06/03/2026					

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : Special Motor

Thermal protection				
ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155°C

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7	
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12	
	Noise	: MG1 - Part 9			
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight, subject to be changed after manufacturing process.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.		
Rev.	Changes Summary		Rev.	Checked	Date
Performed by	martint		Page 2 / 2 Rev. 0		
Checked by					
Date	06/03/2026				