

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : Special Motor

Product code : 19233523

Frame	: 56CZ	Locked rotor time	: 19 s (hot) 34 s (cold)
Output	: 1.5 HP (1.1 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 230/460 V	Altitude	: 3280 ft
Rated current	: 4.56/2.28 A	Protection degree	: IP55
L. R. Amperes	: 36.5/18.2 A	Cooling method	: IC410 - TENV
LRC	: 8.0 Code L	Mounting	: F-1/B34R(D)
No load current	: 3.00/1.50 A	Rotation ¹	: Both
Rated speed	: 1750 rpm	Noise level ²	: -
Slip	: 2.78 %	Vibration class	: A
Rated torque	: 4.50 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 340.0 %	Approx. weight ³	: 41.5 lb
Pull up torque	: 285.0 %	Painting plan	: 207N
Breakdown torque	: 410.0 %	Color	: MUNSELL N 1 - MATTE
Insulation class	: H	Design	: B
Service factor	: 1.00		
Moment of inertia (J)	: 0.1210 sq.ft.lb		

Output	50%	75%	100%	Load type	: -
Efficiency (%)	84.0	86.5	86.5	Load torque	: -
Power Factor	0.46	0.59	0.70	Load inertia (J=GD ² /4)	: -

Bearing type	Drive end	Non drive end	Foundation loads	
	6204-ZZ	6203-ZZ		Max. traction
	Lubrication interval	-		Max. compression
	Lubricant amount	-		
Lubricant type	MOBIL POLYREX EM			

Notes
See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	martint				
Checked by				Page	Rev.
Date	06/03/2026			1 / 2	0

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : Special Motor

Product code : 19233523

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155°C

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date
Performed by	martint			
Checked by			Page	Rev.
Date	06/03/2026		2 / 2	0