

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 Shark - TEFC Premium Efficiency

Frame	: 56C	Locked rotor time	: 19 s (hot) 34 s (cold)
Output	: 1 HP (0.75 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 230/460 V	Altitude	: 3280 ft
Rated current	: 2.94/1.47 A	Protection degree	: IP66
L. R. Amperes	: 25.3/12.6 A	Cooling method	: IC411 - TEFC
LRC	: 8.6	Mounting	: F-1/B14R(D)
No load current	: 1.78/0.890 A	Rotation ¹	: Both
Rated speed	: 1765 rpm	Noise level ²	: 52.0 dB(A)
Slip	: 1.94 %	Vibration class	: A
Rated torque	: 2.94 ft.lb	Starting method	: Direct On Line
Locked rotor torque	: 280 %	Approx. weight ³	: 43.7 lb
Pull up torque	: 235 %	Color	: NO COLOR
Breakdown torque	: 300 %	Design	: B
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.1234 sq.ft.lb		

Output	50%	75%	100%	Load type	: -
Efficiency (%)	82.5	84.0	85.5	Load torque	: -
Power Factor	0.52	0.66	0.75	Load inertia (J=GD ² /4)	: -
Bearing type #1	Drive end 6204-2RS	Non drive end 6203-2RS		Foundation loads	
Lubrication interval	-	-		Max. traction	:
Lubricant amount #1	-	-		Max. compression	:
Lubricant type	MOBIL POLYREX EM				

Notes

See notes on page 2.

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
18.6	16.2	15.3	10.8	7.9	6.3	4.8

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary		Rev.	Checked	Date
Performed by	farazq				1875507899
Checked by	AUTOMATICO				Page Rev.
Date	17/07/2026				1 / 2 0

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 Shark - TEFC Premium Efficiency

Thermal protection ID	Application	Type	Quantity	Sensing Temperature
-----------------------	-------------	------	----------	---------------------

Notes

Standards	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7		
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12		
	Noise	: MG1 - Part 9				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight, subject to be changed after manufacturing process.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.			
Rev.		Changes Summary		Rev.	Checked	Date
Performed by		farazq	1875507899			
Checked by		AUTOMATICO				
Date		17/07/2026				
			Page	Rev.		
			2 / 2	0		