

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12447060

Frame : 254/6TC	Cooling method : IC411 - TEFC
Insulation class : F	Mounting : F-1
Duty cycle : Cont.(S1)	Rotation ¹ : Both (CW and CCW)
Ambient temperature : -20°C to +40°C	Starting method : Direct On Line
Altitude : 1000 m.a.s.l.	Approx. weight ³ : 107 kg
Protection degree : IP55	Moment of inertia (J) : 0.0530 kgm ²
Design : B	

Output [HP]	15	10	10	10	15	15	15
Poles	2	2	2	2	2	2	2
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	34.5/17.2	14.5	14.0	13.7	21.0	19.9	19.3
L. R. Amperes [A]	231/116	109	117	116	107	112	118
LRC [A]	6.7x(Code G)	7.5x(Code J)	8.3x(Code K)	8.5x(Code K)	5.1x(Code E)	5.6x(Code F)	6.1x(Code G)
No load current [A]	10.0/5.00	4.90	5.30	5.50	4.90	5.30	5.50
Rated speed [RPM]	3535	2950	2955	2960	2900	2915	2925
Slip [%]	1.81	1.67	1.50	1.33	3.33	2.83	2.50
Rated torque [kgfm]	3	2	2	2	3	3	3
Locked rotor torque [%]	200	200	229	250	160	180	200
Breakdown torque [%]	260	310	350	380	200	229	240
Service factor	1.25	1.25	1.25	1.25	1.00	1.00	1.15
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	36s (cold) 20s (hot)	50s (cold) 28s (hot)	45s (cold) 25s (hot)	41s (cold) 23s (hot)	25s (cold) 14s (hot)	27s (cold) 15s (hot)	27s (cold) 15s (hot)
Noise level ²	72.0 dB(A)	67.0 dB(A)	67.0 dB(A)	67.0 dB(A)	67.0 dB(A)	67.0 dB(A)	67.0 dB(A)
Efficiency (%)	25%	0.000					
	50%	89.5	90.3	90.1	89.9	89.5	90.2
	75%	91.0	90.5	90.7	90.8	90.2	90.2
	100%	91.0	90.5	90.7	90.8	88.5	89.5
Power Factor	25%	0.00					
	50%	0.77	0.73	0.69	0.67	0.82	0.80
	75%	0.85	0.83	0.80	0.78	0.88	0.87
	100%	0.88	0.87	0.85	0.84	0.90	0.89

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	8.5	9.3	9.3	9.4	7.9	8.5	8.4
	P2 (0,5;1,0)	6.3	6.9	6.9	6.9	5.8	6.3	6.2
	P3 (0,25;1,0)	5.9	6.4	6.4	6.4	5.4	5.8	5.8
	P4 (0,9;0,5)	5.2	5.6	5.6	5.7	4.8	5.1	5.1
	P5 (0,5;0,5)	3.0	3.2	3.2	3.3	2.7	2.9	2.9
	P6 (0,5;0,25)	2.2	2.4	2.4	2.4	2.0	2.2	2.2
	P7 (0,25;0,25)	1.4	1.5	1.5	1.5	1.3	1.4	1.4

	<u>Drive end</u>	<u>Non drive end</u>	Foundation loads
Bearing type :	6309 C3	6209 C3	Max. traction : 80 kgf
Sealing :	V'Ring	V'Ring	Max. compression : 200 kgf
Lubrication interval :	19000 h	20000 h	
Lubricant amount :	13 g	9 g	
Lubricant type :	Mobil Polyrex EM		

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	23/09/2026		Page 1 / 9	Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Notes
USABLE @208V 38.0A SF 1.15 SFA 43.7A

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	23/09/2026				
			2 / 9		

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447060



Performance : 230/460 V 60 Hz 2P

Rated current : 34.5/17.2 A
LRC : 6.7
Rated torque : 3 kgfm
Locked rotor torque : 200 %
Breakdown torque : 260 %
Rated speed : 3535 rpm

Moment of inertia (J) : 0.0530 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 3 / 9	Revision
Checked by					
Date	23/09/2026				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447060



Performance : 380 V 50 Hz 2P IE3

Rated current : 14.5 A
LRC : 7.5
Rated torque : 2 kgfm
Locked rotor torque : 200 %
Breakdown torque : 310 %
Rated speed : 2950 rpm

Moment of inertia (J) : 0.0530 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447060



Performance : 400 V 50 Hz 2P IE3

Rated current	: 14.0 A	Moment of inertia (J)	: 0.0530 kgm ²
LRC	: 8.3	Duty cycle	: Cont.(S1)
Rated torque	: 2 kgfm	Insulation class	: F
Locked rotor torque	: 229 %	Service factor	: 1.25
Breakdown torque	: 350 %	Temperature rise	: 80 K
Rated speed	: 2955 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 9 Revision		
Checked by				
Date	23/09/2026			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447060



Performance : 415 V 50 Hz 2P IE3

Rated current : 13.7 A
LRC : 8.5
Rated torque : 2 kgfm
Locked rotor torque : 250 %
Breakdown torque : 380 %
Rated speed : 2960 rpm

Moment of inertia (J) : 0.0530 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				6 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447060



Performance : 380 V 50 Hz 2P IE1

Rated current : 21.0 A
LRC : 5.1
Rated torque : 3 kgfm
Locked rotor torque : 160 %
Breakdown torque : 200 %
Rated speed : 2900 rpm

Moment of inertia (J) : 0.0530 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	23/09/2026			

Page 7 / 9
Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447060



Performance : 400 V 50 Hz 2P IE2

Rated current : 19.9 A
LRC : 5.6
Rated torque : 3 kgfm
Locked rotor torque : 180 %
Breakdown torque : 229 %
Rated speed : 2915 rpm

Moment of inertia (J) : 0.0530 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 8 / 9	Revision
Checked by					
Date	23/09/2026				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447060



Performance : 415 V 50 Hz 2P IE2

Rated current : 19.3 A
LRC : 6.1
Rated torque : 3 kgfm
Locked rotor torque : 200 %
Breakdown torque : 240 %
Rated speed : 2925 rpm

Moment of inertia (J) : 0.0530 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 9 / 9		
Checked by				
Date	23/09/2026			
		Revision		