

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11402324

Frame	: 364/5TSC	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 374 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.4485 kgm ²
Design	: B		

Output [HP]	60	50	50	50	60	60	60
Poles	2	2	2	2	2	2	2
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	136/67.8	67.4	64.8	62.4	83.1	78.5	75.6
L. R. Amperes [A]	895/447	431	466	462	432	455	477
LRC [A]	6.6x(Code G)	6.4x(Code G)	7.2x(Code H)	7.4x(Code H)	5.2x(Code E)	5.8x(Code F)	6.3x(Code G)
No load current [A]	34.0/17.0	16.6	17.8	18.6	16.6	17.8	18.6
Rated speed [RPM]	3555	2955	2960	2965	2935	2945	2950
Slip [%]	1.25	1.50	1.33	1.17	2.17	1.83	1.67
Rated torque [kgfm]	12	12	12	12	14	14	14
Locked rotor torque [%]	200	190	220	229	160	180	190
Breakdown torque [%]	260	250	280	300	200	229	250
Service factor	1.25	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)
Noise level ²	79.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)
Efficiency (%)	25%						
	50%	92.7	92.1	91.7	91.6	92.4	92.4
	75%	93.6	92.8	92.8	92.9	93.0	93.0
	100%	93.6	93.7	93.7	93.7	92.4	93.0
Power Factor	25%						
	50%	0.81	0.81	0.79	0.76	0.85	0.83
	75%	0.87	0.88	0.86	0.85	0.88	0.88
	100%	0.89	0.89	0.88	0.88	0.89	0.89

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	6.3	6.2	6.2	6.2	7.6	7.0	7.0
	P2 (0,5;1,0)	4.7	4.6	4.6	4.6	5.7	5.2	5.2
	P3 (0,25;1,0)	4.4	4.3	4.3	4.3	5.3	4.9	4.9
	P4 (0,9;0,5)	3.3	3.3	3.3	3.3	4.0	3.6	3.6
	P5 (0,5;0,5)	1.8	1.8	1.8	1.8	2.1	2.0	2.0
	P6 (0,5;0,25)	1.1	1.1	1.1	1.1	1.3	1.2	1.2
	P7 (0,25;0,25)	0.6	0.6	0.6	0.6	0.7	0.7	0.7

Bearing type	Drive end	Non drive end	Foundation loads
	: 6314 C3	: 6314 C3	
	Sealing	Oil Seal	
	: Oil Seal	: Oil Seal	
	Lubrication interval	4000 h	
	: 4000 h	: 4000 h	
Lubricant amount	: 27 g	: 27 g	Max. traction : 232 kgf
	: Mobil Polyrex EM	: Mobil Polyrex EM	
Lubricant type			Max. compression : 597 kgf

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	23/09/2026			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes
USABLE @208V 148A SF 1.10 SFA 163A

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 9		Revision
Checked by					
Date	23/09/2026				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11402324



Performance : 230/460 V 60 Hz 2P

Rated current : 136/67.8 A
 LRC : 6.6
 Rated torque : 12 kgfm
 Locked rotor torque : 200 %
 Breakdown torque : 260 %
 Rated speed : 3555 rpm

Moment of inertia (J) : 0.4485 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K
 Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				3 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11402324



Performance : 380 V 50 Hz 2P IE3

Rated current : 67.4 A
LRC : 6.4
Rated torque : 12 kgfm
Locked rotor torque : 190 %
Breakdown torque : 250 %
Rated speed : 2955 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 4 / 9	Revision
Checked by					
Date	23/09/2026				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11402324



Performance : 400 V 50 Hz 2P IE3

Rated current : 64.8 A
LRC : 7.2
Rated torque : 12 kgfm
Locked rotor torque : 220 %
Breakdown torque : 280 %
Rated speed : 2960 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 9Revision		
Checked by				
Date	23/09/2026			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11402324



Performance : 415 V 50 Hz 2P IE3

Rated current : 62.4 A
LRC : 7.4
Rated torque : 12 kgfm
Locked rotor torque : 229 %
Breakdown torque : 300 %
Rated speed : 2965 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 6 / 9	Revision
Checked by					
Date	23/09/2026				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11402324



Performance : 380 V 50 Hz 2P IE1

Rated current : 83.1 A
LRC : 5.2
Rated torque : 14 kgfm
Locked rotor torque : 160 %
Breakdown torque : 200 %
Rated speed : 2935 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 7 / 9	Revision
Checked by					
Date	23/09/2026				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11402324



Performance : 400 V 50 Hz 2P IE2

Rated current : 78.5 A
LRC : 5.8
Rated torque : 14 kgfm
Locked rotor torque : 180 %
Breakdown torque : 229 %
Rated speed : 2945 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 8 / 9	Revision
Checked by					
Date	23/09/2026				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11402324



Performance : 415 V 50 Hz 2P IE2

Rated current : 75.6 A
LRC : 6.3
Rated torque : 14 kgfm
Locked rotor torque : 190 %
Breakdown torque : 250 %
Rated speed : 2950 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 9 / 9 Revision		
Checked by				
Date	23/09/2026			