

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :					
Product line		: Standard Efficiency Three-Phase	Product code :	13293056	
Frame	: 56	Cooling method	: IC411 - TEFC		
Insulation class	: F	Mounting	: F-1		
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)		
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line		
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 12.5 kg		
Protection degree	: IP55	Moment of inertia (J)	: 0.0036 kgm ²		
Design	: A				
Output [HP]	1	1	1		
Poles	4	4	4		
Frequency [Hz]	60	50	50		
Rated voltage [V]	230/460	190/380	220/415		
Rated current [A]	3.32/1.66	3.68/1.84	3.58/1.90		
L. R. Amperes [A]	25.6/12.8	23.2/11.6	24.0/12.7		
LRC [A]	7.7x(Code M)	6.3x(Code J)	6.7x(Code L)		
No load current [A]	2.40/1.20	2.35/1.18	2.88/1.53		
Rated speed [RPM]	1760	1445	1455		
Slip [%]	2.22	3.67	3.00		
Rated torque [kgfm]	0.412	0.502	0.499		
Locked rotor torque [%]	270	200	250		
Breakdown torque [%]	300	260	310		
Service factor		1.15	1.15		
Temperature rise	80 K	80 K	80 K		
Locked rotor time	21s (cold) 12s (hot)	0s (cold) 0s (hot)	0s (cold) 0s (hot)		
Noise level ²	52.0 dB(A)	49.0 dB(A)	49.0 dB(A)		
Efficiency (%)	25%				
	50%	74.0	74.9	69.9	
	75%	78.5	78.1	75.4	
	100%	80.0	78.3	77.3	
Power Factor	25%				
	50%	0.48	0.57	0.47	
	75%	0.62	0.71	0.61	
	100%	0.71	0.79	0.71	
Bearing type	: Drive end 6204 ZZ Non drive end 6202 ZZ	Foundation loads			
Sealing	: V'Ring V'Ring	Max. traction	: 43 kgf		
Lubrication interval	: - -	Max. compression	: 56 kgf		
Lubricant amount	: - -				
Lubricant type	: Mobil Polyrex EM				
Notes USABLE @208V 3.67A SF 1.00 SFA 3.67A					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	11/05/2022			1 / 4	


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Standard Efficiency Three-Phase Product code : 13293056



Performance : 230/460 V 60 Hz 4P

Rated current : 3.32/1.66 A
 LRC : 7.7
 Rated torque : 0.412 kgfm
 Locked rotor torque : 270 %
 Breakdown torque : 300 %
 Rated speed : 1760 rpm

Moment of inertia (J) : 0.0036 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor :
 Temperature rise : 80 K
 Design : A

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : Standard Efficiency Three-Phase Product code : 13293056



Performance : 190/380 V 50 Hz 4P

Rated current : 3.68/1.84 A
 LRC : 6.3
 Rated torque : 0.502 kgfm
 Locked rotor torque : 200 %
 Breakdown torque : 260 %
 Rated speed : 1445 rpm

Moment of inertia (J) : 0.0036 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : A

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Standard Efficiency Three-Phase Product code : 13293056



Performance : 220/415 V 50 Hz 4P

Rated current : 3.58/1.90 A
 LRC : 6.7
 Rated torque : 0.499 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 310 %
 Rated speed : 1455 rpm

Moment of inertia (J) : 0.0036 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K
 Design : A

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 4	Revision
Checked by				
Date	11/05/2022			