

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer	:				
Product line	: Standard Efficiency Three-Phase	Product code :	13942727		
Frame	: W56C	Cooling method	: IC01 - ODP		
Insulation class	: F	Mounting	: F-1		
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)		
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line		
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 8.7 kg		
		Moment of inertia (J)	: 0.0019 kgm ²		
Output [HP]	0.75				
Poles	4				
Frequency [Hz]	60				
Rated voltage [V]	575				
Rated current [A]	1.01				
L. R. Amperes [A]	5.95				
LRC [A]	5.9x(Code J)				
No load current [A]	0.827				
Rated speed [RPM]	1730				
Slip [%]	3.89				
Rated torque [kgfm]	0.315				
Locked rotor torque [%]	240				
Breakdown torque [%]	280				
Service factor	1.25				
Temperature rise	80 K				
Locked rotor time	18s (cold) 10s (hot)				
Noise level ²	50.0 dB(A)				
Efficiency (%)	25%				
	50%	66.0			
	75%	72.0			
	100%	74.0			
Power Factor	25%				
	50%	0.50			
	75%	0.63			
	100%	0.74			
Bearing type	: <u>Drive end</u> 6203 ZZ	<u>Non drive end</u> 6202 ZZ	Foundation loads		
Sealing	: Without	Without	Max. traction	: 24 kgf	
	Bearing Seal	Bearing Seal	Max. compression	: 32 kgf	
Lubrication interval	: -	-			
Lubricant amount	: -	-			
Lubricant type	: Mobil Polyrex EM				
Notes					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	17/05/2022			1 / 2	


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Standard Efficiency Three-Phase Product code : 13942727



Performance : 575 V 60 Hz 4P

Rated current	: 1.01 A	Moment of inertia (J)	: 0.0019 kgm ²
LRC	: 5.9	Duty cycle	: Cont.(S1)
Rated torque	: 0.315 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	: 1.25
Breakdown torque	: 280 %	Temperature rise	: 80 K
Rated speed	: 1730 rpm		

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	17/05/2022			