

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer	:				
Product line	: Single-Phase	Product code :	13400614		
Frame	: 56H	Cooling method	: IC411 - TEFC		
Insulation class	: F	Mounting	: F-1		
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)		
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line		
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 18.9 kg		
Protection degree	: IP55	Moment of inertia (J)	: 0.0067 kgm ²		
Design	: L				
Output [HP]	0.75				
Poles	6				
Frequency [Hz]	60				
Rated voltage [V]	115/208-230				
Rated current [A]	9.40/5.20-4.70				
L. R. Amperes [A]	60.2/33.3-30.1				
LRC [A]	6.4x(Code L)				
No load current [A]	6.00/2.59-3.00				
Rated speed [RPM]	1170				
Slip [%]	2.50				
Rated torque [kgfm]	0.465				
Locked rotor torque [%]	220				
Breakdown torque [%]	240				
Service factor					
Temperature rise	80 K				
Locked rotor time	27s (cold) 15s (hot)				
Noise level ²	54.0 dB(A)				
Efficiency (%)	25%				
	50%	59.0			
	75%	67.0			
	100%	70.0			
Power Factor	25%				
	50%	0.58			
	75%	0.67			
	100%	0.73			
Bearing type	: Drive end	6203 ZZ	Non drive end	6202 ZZ	
Sealing	: V'Ring		V'Ring		
Lubrication interval	: -		-		
Lubricant amount	: -		-		
Lubricant type	: Mobil Polyrex EM				
Foundation loads	Max. traction : 26 kgf				
	Max. compression : 45 kgf				
Notes					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	17/05/2022			1 / 2	

LOAD PERFORMANCE CURVE

Single Phase Induction Motor - Squirrel Cage




Customer :

Product line : Single-Phase

Product code : 13400614

LOAD PERFORMANCE CURVE



Performance : 115/208-230 V 60 Hz 6P

Rated current : 9.40/5.20-4.70 A
 LRC : 6.4
 Rated torque : 0.465 kgfm
 Locked rotor torque : 220 %
 Breakdown torque : 240 %
 Rated speed : 1170 rpm

Moment of inertia (J) : 0.0067 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor :
 Temperature rise : 80 K
 Design : L

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	17/05/2022			