

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :							
Product line	: W22 NEMA Premium Efficiency Three-Phase	Product code :	12378663				
Frame	: 143/5T	Cooling method	: IC411 - TEFC				
Insulation class	: F	Mounting	: F-1				
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)				
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line				
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 17.7 kg				
Protection degree	: IP55	Moment of inertia (J)	: 0.0014 kgm ²				
Output [HP]	1	0.75	0.75	0.75	1	1	1
Poles	2	2	2	2	2	2	2
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	2.94/1.47	1.34	1.32	1.33	1.71	1.65	1.63
L. R. Amperes [A]	24.1/12.1	11.5	11.9	12.5	11.5	11.9	12.6
LRC [A]	8.2x(Code L)	8.6x(Code M)	9.0x(Code M)	9.4x(Code N)	6.7x(Code J)	7.2x(Code K)	7.7x(Code L)
No load current [A]	1.54/0.770	0.740	0.820	0.880	0.740	0.820	0.880
Rated speed [RPM]	3500	2910	2920	2925	2865	2885	2895
Slip [%]	2.78	3.00	2.67	2.50	4.50	3.83	3.50
Rated torque [kgfm]	0.207	0.187	0.186	0.186	0.253	0.252	0.251
Locked rotor torque [%]	220	229	250	270	170	190	200
Breakdown torque [%]	310	310	340	360	220	250	270
Service factor	1.25	1.25	1.25	1.25	1.25	1.25	1.25
Temperature rise	80 K	80 K	80 K	80 K	80 K	80 K	80 K
Locked rotor time	36s (cold) 20s (hot)	46s (cold) 26s (hot)	43s (cold) 24s (hot)	39s (cold) 22s (hot)	39s (cold) 22s (hot)	36s (cold) 20s (hot)	36s (cold) 20s (hot)
Noise level ²	68.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)
Efficiency (%)	25%						
	50%	75.0	72.9	72.3	71.7	77.0	77.0
	75%	79.0	77.6	77.6	77.6	78.5	78.5
	100%	80.0	80.0	80.0	80.0	78.5	80.0
Power Factor	25%						
	50%	0.63	0.58	0.53	0.50	0.68	0.63
	75%	0.74	0.70	0.66	0.63	0.78	0.75
	100%	0.80	0.78	0.75	0.72	0.85	0.82
Losses at normative operating points (speed;torque), in percentage of rated output power							
Losses (%)	P1 (0,9;1,0)	22.8	22.8	22.8	22.8	22.8	22.8
	P2 (0,5;1,0)	16.9	16.9	16.9	16.9	16.9	16.9
	P3 (0,25;1,0)	16.0	16.0	16.0	16.0	16.0	16.0
	P4 (0,9;0,5)	14.5	14.5	14.5	14.5	14.5	14.5
	P5 (0,5;0,5)	8.4	8.4	8.4	8.4	8.4	8.4
	P6 (0,5;0,25)	6.7	6.7	6.7	6.7	6.7	6.7
	P7 (0,25;0,25)	4.4	4.4	4.4	4.4	4.4	4.4
Bearing type	: Drive end : 6205 ZZ Non drive end : 6204 ZZ	Foundation loads	Max. traction : 10 kgf Max. compression : 28 kgf				
Sealing	: V'Ring V'Ring						
Lubrication interval	: - -						
Lubricant amount	: - -						
Lubricant type	: Mobil Polyrex EM						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A).				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.	Changes Summary			Performed	Checked	Date	
Performed by							
Checked by					Page	Revision	
Date	20/10/2024				1 / 9		

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes
USABLE @208V 3.16A SF 1.15 SFA 3.64A

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	20/10/2024		2 / 9	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12378663



Performance : 230/460 V 60 Hz 2P

Rated current : 2.94/1.47 A
 LRC : 8.2
 Rated torque : 0.207 kgfm
 Locked rotor torque : 220 %
 Breakdown torque : 310 %
 Rated speed : 3500 rpm

Moment of inertia (J) : 0.0014 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		3 / 9		
Date		20/10/2024		

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12378663

LOAD PERFORMANCE CURVE



Performance : 380 V 50 Hz 2P IE3

Rated current	: 1.34 A	Moment of inertia (J)	: 0.0014 kgm ²
LRC	: 8.6	Duty cycle	: Cont.(S1)
Rated torque	: 0.187 kgfm	Insulation class	: F
Locked rotor torque	: 229 %	Service factor	: 1.25
Breakdown torque	: 310 %	Temperature rise	: 80 K
Rated speed	: 2910 rpm		

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 4 / 9	Revision
Checked by				
Date	20/10/2024			


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12378663



Performance : 400 V 50 Hz 2P IE3

Rated current : 1.32 A
 LRC : 9.0
 Rated torque : 0.186 kgfm
 Locked rotor torque : 250 %
 Breakdown torque : 340 %
 Rated speed : 2920 rpm

Moment of inertia (J) : 0.0014 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 5 / 9	Revision
Checked by				
Date	20/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12378663

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 2P IE3

Rated current : 1.33 A
 LRC : 9.4
 Rated torque : 0.186 kgfm
 Locked rotor torque : 270 %
 Breakdown torque : 360 %
 Rated speed : 2925 rpm

Moment of inertia (J) : 0.0014 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 6 / 9	Revision
Checked by				
Date	20/10/2024			


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12378663



Performance : 380 V 50 Hz 2P IE2

Rated current : 1.71 A
 LRC : 6.7
 Rated torque : 0.253 kgfm
 Locked rotor torque : 170 %
 Breakdown torque : 220 %
 Rated speed : 2865 rpm

Moment of inertia (J) : 0.0014 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 7 / 9	Revision
Checked by				
Date	20/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12378663

LOAD PERFORMANCE CURVE



Performance : 400 V 50 Hz 2P IE2

Rated current	: 1.65 A	Moment of inertia (J)	: 0.0014 kgm ²
LRC	: 7.2	Duty cycle	: Cont.(S1)
Rated torque	: 0.252 kgfm	Insulation class	: F
Locked rotor torque	: 190 %	Service factor	: 1.25
Breakdown torque	: 250 %	Temperature rise	: 80 K
Rated speed	: 2885 rpm		

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 8 / 9	Revision
Checked by				
Date	20/10/2024			


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12378663



Performance : 415 V 50 Hz 2P IE2

Rated current : 1.63 A
 LRC : 7.7
 Rated torque : 0.251 kgfm
 Locked rotor torque : 200 %
 Breakdown torque : 270 %
 Rated speed : 2895 rpm

Moment of inertia (J) : 0.0014 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.25
 Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 9 / 9	Revision
Checked by				
Date	20/10/2024			