

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11723870

Frame : 182/4T	Cooling method : IC411 - TEFC
Insulation class : F	Mounting : F-1
Duty cycle : Cont.(S1)	Rotation <sup>1</sup> : Both (CW and CCW)
Ambient temperature : -20°C to +40°C	Starting method : Direct On Line
Altitude : 1000 m.a.s.l.	Approx. weight <sup>3</sup> : 39.0 kg
Protection degree : IP55	Moment of inertia (J) : 0.0143 kgm <sup>2</sup>
Design : B	

Output [HP]	3	3	3	3
Poles	4	4	4	4
Frequency [Hz]	60	50	50	50
Rated voltage [V]	230/460	380	400	415
Rated current [A]	7.82/3.91	4.78	4.54	4.43
L. R. Amperes [A]	63.3/31.7	30.1	32.2	33.7
LRC [A]	8.1x(Code K)	6.3x(Code H)	7.1x(Code J)	7.6x(Code K)
No load current [A]	4.00/2.00	2.00	2.10	2.25
Rated speed [RPM]	1760	1445	1450	1455
Slip [%]	2.22	3.67	3.33	3.00
Rated torque [kgfm]	1.24	1.51	1.50	1.50
Locked rotor torque [%]	220	220	220	240
Breakdown torque [%]	330	250	290	320
Service factor	1.25	1.25	1.25	1.25
Temperature rise	80 K	80 K	80 K	80 K
Locked rotor time	41s (cold) 23s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)
Noise level <sup>2</sup>	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)
Efficiency (%)	25%			
	50%	87.5	87.5	87.5
	75%	88.5	87.5	87.5
	100%	89.5	87.5	87.5
Power Factor	25%			
	50%	0.61	0.68	0.64
	75%	0.71	0.77	0.73
	100%	0.79	0.80	0.79

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	11.0	13.4	13.4	13.4
	P2 (0,5;1,0)	8.9	10.8	10.8	10.8
	P3 (0,25;1,0)	8.8	10.7	10.7	10.7
	P4 (0,9;0,5)	6.1	7.4	7.4	7.4
	P5 (0,5;0,5)	4.0	4.9	4.9	4.9
	P6 (0,5;0,25)	3.0	3.6	3.6	3.6
	P7 (0,25;0,25)	2.1	2.6	2.6	2.6

	<u>Drive end</u>	<u>Non drive end</u>	Foundation loads
Bearing type :	6207 ZZ	6206 ZZ	Max. traction : 81 kgf
Sealing :	V'Ring	V'Ring	Max. compression : 120 kgf
Lubrication interval :	-	-	
Lubricant amount :	-	-	
Lubricant type :	Mobil Polyrex EM		

This revision replaces and cancel the previous one, which must be eliminated.  
 (1) Looking the motor from the shaft end.  
 (2) Measured at 1m and with tolerance of +3dB(A).  
 (3) Approximate weight subject to changes after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	20/10/2024		Page 1 / 6	Revision

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : \_\_\_\_\_

Notes  
USABLE @208V 8.65A SF 1.15 SFA 9.95A

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 6		Revision
Checked by					
Date	20/10/2024				

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency  
Three-Phase

Product code : 11723870



Performance : 230/460 V 60 Hz 4P

Rated current : 7.82/3.91 A  
LRC : 8.1  
Rated torque : 1.24 kgfm  
Locked rotor torque : 220 %  
Breakdown torque : 330 %  
Rated speed : 1760 rpm

Moment of inertia (J) : 0.0143 kgm<sup>2</sup>  
Duty cycle : Cont.(S1)  
Insulation class : F  
Service factor : 1.25  
Temperature rise : 80 K  
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 3 / 6Revision			
Checked by					
Date	20/10/2024				

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency  
Three-Phase

Product code : 11723870



Performance : 380 V 50 Hz 4P IE3

Rated current : 4.78 A  
LRC : 6.3  
Rated torque : 1.51 kgfm  
Locked rotor torque : 220 %  
Breakdown torque : 250 %  
Rated speed : 1445 rpm

Moment of inertia (J) : 0.0143 kgm<sup>2</sup>  
Duty cycle : Cont.(S1)  
Insulation class : F  
Service factor : 1.25  
Temperature rise : 80 K  
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 4 / 6	Revision
Checked by					
Date	20/10/2024				

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency  
Three-Phase

Product code : 11723870



Performance : 400 V 50 Hz 4P IE3

Rated current : 4.54 A  
LRC : 7.1  
Rated torque : 1.50 kgfm  
Locked rotor torque : 220 %  
Breakdown torque : 290 %  
Rated speed : 1450 rpm

Moment of inertia (J) : 0.0143 kgm<sup>2</sup>  
Duty cycle : Cont.(S1)  
Insulation class : F  
Service factor : 1.25  
Temperature rise : 80 K  
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 5 / 6	Revision
Checked by					
Date	20/10/2024				

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase      Product code : 11723870

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 4P IE3

Rated current	: 4.43 A	Moment of inertia (J)	: 0.0143 kgm <sup>2</sup>
LRC	: 7.6	Duty cycle	: Cont.(S1)
Rated torque	: 1.50 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	: 1.25
Breakdown torque	: 320 %	Temperature rise	: 80 K
Rated speed	: 1455 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 6 / 6      Revision			
Checked by					
Date	20/10/2024				