

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11441772

Frame : 284/6T	Cooling method : IC411 - TEFC
Insulation class : F	Mounting : F-1
Duty cycle : Cont.(S1)	Rotation ¹ : Both (CW and CCW)
Ambient temperature : -20°C to +40°C	Starting method : Direct On Line
Altitude : 1000 m.a.s.l.	Approx. weight ³ : 199 kg
Protection degree : IP55	Moment of inertia (J) : 0.3861 kgm ²
Design : B	

Output [HP]	20	15	15	15	20	20	20
Poles	6	6	6	6	6	6	6
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	48.4/24.2	22.0	21.2	20.8	29.9	28.1	27.2
L. R. Amperes [A]	300/150	147	155	156	141	149	158
LRC [A]	6.2x(Code G)	6.7x(Code H)	7.3x(Code J)	7.5x(Code J)	4.7x(Code E)	5.3x(Code F)	5.8x(Code G)
No load current [A]	19.0/9.50	9.40	10.0	10.6	9.40	10.0	10.6
Rated speed [RPM]	1175	980	982	983	965	970	975
Slip [%]	2.08	2.00	1.80	1.70	3.50	3.00	2.50
Rated torque [kgfm]	12.4	11.1	11.1	11.1	15.0	15.0	14.9
Locked rotor torque [%]	229	229	270	280	170	200	210
Breakdown torque [%]	260	270	290	320	200	220	240
Service factor	1.25	1.00	1.15	1.15	1.00	1.15	1.15
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	80 K
Locked rotor time	28s (cold) 16s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)
Noise level ²	59.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)
Efficiency (%)	25%						
	50%	91.0	90.0	89.3	89.3	90.2	90.2
	75%	91.7	90.3	90.3	90.6	90.2	90.2
	100%	91.7	90.3	90.3	90.8	88.5	89.5
Power Factor	25%						
	50%	0.70	0.66	0.63	0.60	0.76	0.73
	75%	0.80	0.79	0.76	0.73	0.83	0.82
	100%	0.85	0.84	0.83	0.81	0.86	0.86

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	8.7	8.7	8.7	8.7	8.7	8.7
	P2 (0,5;1,0)	7.1	7.1	7.1	7.1	7.1	7.1
	P3 (0,25;1,0)	6.9	6.9	6.9	6.9	6.9	6.9
	P4 (0,9;0,5)	4.3	4.3	4.3	4.3	4.3	4.3
	P5 (0,5;0,5)	2.8	2.8	2.8	2.8	2.8	2.8
	P6 (0,5;0,25)	1.9	1.9	1.9	1.9	1.9	1.9
	P7 (0,25;0,25)	1.2	1.2	1.2	1.2	1.2	1.2

Bearing type : 6311 C3	Non drive end : 6211 C3	Foundation loads
Sealing : V'Ring	V'Ring	Max. traction : 412 kgf
Lubrication interval : 20000 h	20000 h	Max. compression : 610 kgf
Lubricant amount : 18 g	11 g	
Lubricant type : Mobil Polyrex EM		

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	21/10/2024		Page 1 / 9	Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes
USABLE @208V 53.5A SF 1.15 SFA 61.5A

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 9		Revision
Checked by					
Date	21/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11441772



Performance : 230/460 V 60 Hz 6P

Rated current : 48.4/24.2 A
LRC : 6.2
Rated torque : 12.4 kgfm
Locked rotor torque : 229 %
Breakdown torque : 260 %
Rated speed : 1175 rpm

Moment of inertia (J) : 0.3861 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 3 / 9	Revision
Checked by					
Date	21/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11441772



Performance : 380 V 50 Hz 6P IE3

Rated current : 22.0 A
LRC : 6.7
Rated torque : 11.1 kgfm
Locked rotor torque : 229 %
Breakdown torque : 270 %
Rated speed : 980 rpm

Moment of inertia (J) : 0.3861 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11441772



Performance : 400 V 50 Hz 6P IE3

Rated current : 21.2 A
LRC : 7.3
Rated torque : 11.1 kgfm
Locked rotor torque : 270 %
Breakdown torque : 290 %
Rated speed : 982 rpm

Moment of inertia (J) : 0.3861 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 9Revision		
Checked by				
Date	21/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11441772



Performance : 415 V 50 Hz 6P IE3

Rated current : 20.8 A
LRC : 7.5
Rated torque : 11.1 kgfm
Locked rotor torque : 280 %
Breakdown torque : 320 %
Rated speed : 983 rpm

Moment of inertia (J) : 0.3861 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				6 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11441772



Performance : 380 V 50 Hz 6P IE1

Rated current	: 29.9 A	Moment of inertia (J)	: 0.3861 kgm ²
LRC	: 4.7	Duty cycle	: Cont.(S1)
Rated torque	: 15.0 kgfm	Insulation class	: F
Locked rotor torque	: 170 %	Service factor	: 1.00
Breakdown torque	: 200 %	Temperature rise	: 105 K
Rated speed	: 965 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 7 / 9 Revision		
Checked by				
Date	21/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11441772

LOAD PERFORMANCE CURVE



Performance : 400 V 50 Hz 6P IE1

Rated current	: 28.1 A	Moment of inertia (J)	: 0.3861 kgm ²
LRC	: 5.3	Duty cycle	: Cont.(S1)
Rated torque	: 15.0 kgfm	Insulation class	: F
Locked rotor torque	: 200 %	Service factor	: 1.15
Breakdown torque	: 220 %	Temperature rise	: 105 K
Rated speed	: 970 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 8 / 9	Revision
Checked by					
Date	21/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11441772



Performance : 415 V 50 Hz 6P IE2

Rated current	: 27.2 A	Moment of inertia (J)	: 0.3861 kgm ²
LRC	: 5.8	Duty cycle	: Cont.(S1)
Rated torque	: 14.9 kgfm	Insulation class	: F
Locked rotor torque	: 210 %	Service factor	: 1.15
Breakdown torque	: 240 %	Temperature rise	: 80 K
Rated speed	: 975 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 9 / 9		
Checked by				
Date	21/10/2024			
		Revision		