

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11355769

Frame : 444/5T	Cooling method : IC411 - TEFC
Insulation class : F	Mounting : F-1
Duty cycle : Cont.(S1)	Rotation ¹ : Both (CW and CCW)
Ambient temperature : -20°C to +40°C	Starting method : Direct On Line
Altitude : 1000 m.a.s.l.	Approx. weight ³ : 702 kg
Protection degree : IP55	Moment of inertia (J) : 2.41 kgm ²
Design : B	

Output [HP]	125	100	100	100	125	125	125
Poles	4	4	4	4	4	4	4
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	279/139	141	136	132	168	162	155
L. R. Amperes [A]	1811/905	903	950	1004	858	922	977
LRC [A]	6.5x(Code G)	6.4x(Code G)	7.0x(Code H)	7.6x(Code J)	5.1x(Code E)	5.7x(Code F)	6.3x(Code G)
No load current [A]	92.0/46.0	46.0	49.0	52.0	44.0	49.0	52.0
Rated speed [RPM]	1785	1485	1485	1487	1480	1482	1483
Slip [%]	0.83	1.00	1.00	0.87	1.33	1.20	1.13
Rated torque [kgfm]	50.8	48.9	48.9	48.8	61.3	61.2	61.2
Locked rotor torque [%]	200	190	220	240	160	180	190
Breakdown torque [%]	229	229	260	280	200	200	220
Service factor	1.15	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	80 K	80 K	80 K
Locked rotor time	48s (cold) 27s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)
Noise level ²	73.0 dB(A)	69.0 dB(A)	69.0 dB(A)	69.0 dB(A)	69.0 dB(A)	69.0 dB(A)	69.0 dB(A)
Efficiency (%)	25%						
	50%	95.0	94.7	94.6	94.3	95.0	95.0
	75%	95.4	95.1	95.1	95.1	95.0	95.0
	100%	95.4	95.0	95.0	95.2	94.5	95.0
Power Factor	25%						
	50%	0.74	0.73	0.69	0.67	0.79	0.74
	75%	0.82	0.82	0.80	0.78	0.84	0.83
	100%	0.85	0.85	0.84	0.83	0.86	0.85

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	4.5	4.9	4.9	4.7	5.5	5.5	4.9
	P2 (0,5;1,0)	3.4	3.7	3.7	3.5	4.1	4.1	3.7
	P3 (0,25;1,0)	3.0	3.3	3.3	3.1	3.6	3.6	3.3
	P4 (0,9;0,5)	2.4	2.6	2.6	2.5	2.9	2.9	2.6
	P5 (0,5;0,5)	1.4	1.5	1.5	1.5	1.7	1.7	1.5
	P6 (0,5;0,25)	0.9	1.0	1.0	1.0	1.1	1.1	1.0
	P7 (0,25;0,25)	0.6	0.6	0.6	0.6	0.7	0.7	0.6

	<u>Drive end</u>	<u>Non drive end</u>	Foundation loads
Bearing type :	6319 C3	6316 C3	Max. traction : 826 kgf
Sealing :	WSeal	WSeal	Max. compression : 1528 kgf
Lubrication interval :	8000 h	10000 h	
Lubricant amount :	45 g	34 g	
Lubricant type :	Mobil Polyrex EM		

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	21/10/2024		Page 1 / 9	Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Notes
USABLE @208V 307A SF 1.00 SFA 307A

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 9		Revision
Checked by					
Date	21/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11355769



Performance : 230/460 V 60 Hz 4P

Rated current : 279/139 A
LRC : 6.5
Rated torque : 50.8 kgfm
Locked rotor torque : 200 %
Breakdown torque : 229 %
Rated speed : 1785 rpm

Moment of inertia (J) : 2.41 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by					
Date					
	21/10/2024			3 / 9	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11355769

LOAD PERFORMANCE CURVE



Performance : 380 V 50 Hz 4P IE3			
Rated current	: 141 A	Moment of inertia (J)	: 2.41 kgm ²
LRC	: 6.4	Duty cycle	: Cont.(S1)
Rated torque	: 48.9 kgfm	Insulation class	: F
Locked rotor torque	: 190 %	Service factor	: 1.00
Breakdown torque	: 229 %	Temperature rise	: 80 K
Rated speed	: 1485 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 4 / 9	Revision
Checked by					
Date	21/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11355769



Performance : 400 V 50 Hz 4P IE3

Rated current : 136 A
LRC : 7.0
Rated torque : 48.9 kgfm
Locked rotor torque : 220 %
Breakdown torque : 260 %
Rated speed : 1485 rpm

Moment of inertia (J) : 2.41 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 9Revision		
Checked by				
Date	21/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11355769

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 4P IE3			
Rated current	: 132 A	Moment of inertia (J)	: 2.41 kgm ²
LRC	: 7.6	Duty cycle	: Cont.(S1)
Rated torque	: 48.8 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	: 1.00
Breakdown torque	: 280 %	Temperature rise	: 80 K
Rated speed	: 1487 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 6 / 9	Revision
Checked by					
Date	21/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11355769



Performance : 380 V 50 Hz 4P IE2

Rated current : 168 A
LRC : 5.1
Rated torque : 61.3 kgfm
Locked rotor torque : 160 %
Breakdown torque : 200 %
Rated speed : 1480 rpm

Moment of inertia (J) : 2.41 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	21/10/2024			

Page

7 / 9

Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11355769

LOAD PERFORMANCE CURVE



Performance : 400 V 50 Hz 4P IE2			
Rated current	: 162 A	Moment of inertia (J)	: 2.41 kgm ²
LRC	: 5.7	Duty cycle	: Cont.(S1)
Rated torque	: 61.2 kgfm	Insulation class	: F
Locked rotor torque	: 180 %	Service factor	: 1.00
Breakdown torque	: 200 %	Temperature rise	: 80 K
Rated speed	: 1482 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 8 / 9	Revision
Checked by					
Date	21/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11355769



Performance : 415 V 50 Hz 4P IE2

Rated current : 155 A
LRC : 6.3
Rated torque : 61.2 kgfm
Locked rotor torque : 190 %
Breakdown torque : 220 %
Rated speed : 1483 rpm

Moment of inertia (J) : 2.41 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 9 / 9Revision		
Checked by				
Date	21/10/2024			