

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 13334675

Frame	: 254/6T	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 130 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.0647 kgm ²
Design	: B		

Output [HP]	20	15	15	15	20	20	20
Poles	2	2	2	2	2	2	2
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	460	380	400	415	380	400	415
Rated current [A]	23.3	20.8	20.0	19.5	28.6	27.2	26.0
L. R. Amperes [A]	142	146	154	158	146	155	159
LRC [A]	6.1x(Code G)	7.0x(Code H)	7.7x(Code J)	8.1x(Code J)	5.1x(Code E)	5.7x(Code F)	6.1x(Code G)
No load current [A]	6.50	6.20	6.60	6.90	6.20	6.60	6.90
Rated speed [RPM]	3520	2925	2935	2940	2870	2905	2915
Slip [%]	2.22	2.50	2.17	2.00	4.33	3.17	2.83
Rated torque [kgfm]	4.12	3.72	3.71	3.70	5.06	5.00	4.98
Locked rotor torque [%]	220	220	240	270	160	180	200
Breakdown torque [%]	250	260	280	310	200	210	229
Service factor	1.25	1.15	1.15	1.15	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	34s (cold) 19s (hot)	28s (cold) 16s (hot)	28s (cold) 16s (hot)	28s (cold) 16s (hot)	14s (cold) 8s (hot)	18s (cold) 10s (hot)	21s (cold) 12s (hot)
Noise level ²	72.0 dB(A)	67.0 dB(A)	67.0 dB(A)	67.0 dB(A)	67.0 dB(A)	67.0 dB(A)	67.0 dB(A)
Efficiency (%)	25%						
	50%	91.0	90.6	90.4	89.8	91.0	91.0
	75%	91.7	90.9	91.2	91.1	90.2	91.0
	100%	91.0	91.2	91.2	91.2	88.5	89.5
Power Factor	25%						
	50%	0.80	0.78	0.75	0.73	0.85	0.83
	75%	0.87	0.86	0.85	0.83	0.89	0.88
	100%	0.89	0.88	0.87	0.86	0.90	0.89

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	9.0	8.8	8.8	8.8	11.9	10.7	9.9
	P2 (0,5;1,0)	7.0	6.8	6.8	6.8	9.2	8.3	7.7
	P3 (0,25;1,0)	6.8	6.6	6.6	6.6	8.9	8.1	7.5
	P4 (0,9;0,5)	4.6	4.5	4.5	4.5	6.0	5.4	5.0
	P5 (0,5;0,5)	2.6	2.5	2.5	2.5	3.4	3.1	2.8
	P6 (0,5;0,25)	1.6	1.5	1.5	1.5	2.1	1.9	1.7
	P7 (0,25;0,25)	0.9	0.9	0.9	0.9	1.2	1.1	1.0

Bearing type	: 6309 C3	Non drive end	6209 C3	Foundation loads	
Sealing	: Taconite		Taconite	Max. traction	: 115 kgf
	: Labyrinth		Labyrinth	Max. compression	: 245 kgf
Lubrication interval	: 19000 h		20000 h		
Lubricant amount	: 13 g		9 g		
Lubricant type	: Mobil Polyrex EM				

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	22/10/2024		Page 1 / 9	Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 13334675



Performance : 460 V 60 Hz 2P

Rated current : 23.3 A
LRC : 6.1
Rated torque : 4.12 kgfm
Locked rotor torque : 220 %
Breakdown torque : 250 %
Rated speed : 3520 rpm

Moment of inertia (J) : 0.0647 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 9Revision		
Checked by				
Date	22/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 13334675



Performance : 380 V 50 Hz 2P IE3

Rated current : 20.8 A
LRC : 7.0
Rated torque : 3.72 kgfm
Locked rotor torque : 220 %
Breakdown torque : 260 %
Rated speed : 2925 rpm

Moment of inertia (J) : 0.0647 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 4 / 9	Revision
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 13334675



Performance : 400 V 50 Hz 2P IE3

Rated current : 20.0 A
LRC : 7.7
Rated torque : 3.71 kgfm
Locked rotor torque : 240 %
Breakdown torque : 280 %
Rated speed : 2935 rpm

Moment of inertia (J) : 0.0647 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 9 Revision		
Checked by				
Date	22/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 13334675



Performance : 415 V 50 Hz 2P IE3

Rated current : 19.5 A
LRC : 8.1
Rated torque : 3.70 kgfm
Locked rotor torque : 270 %
Breakdown torque : 310 %
Rated speed : 2940 rpm

Moment of inertia (J) : 0.0647 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				6 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 13334675



Performance : 380 V 50 Hz 2P

Rated current : 28.6 A
LRC : 5.1
Rated torque : 5.06 kgfm
Locked rotor torque : 160 %
Breakdown torque : 200 %
Rated speed : 2870 rpm

Moment of inertia (J) : 0.0647 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 7 / 9	Revision
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 13334675



Performance : 400 V 50 Hz 2P IE1

Rated current : 27.2 A
LRC : 5.7
Rated torque : 5.00 kgfm
Locked rotor torque : 180 %
Breakdown torque : 210 %
Rated speed : 2905 rpm

Moment of inertia (J) : 0.0647 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 8 / 9	Revision
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 13334675



Performance : 415 V 50 Hz 2P IE1

Rated current : 26.0 A
LRC : 6.1
Rated torque : 4.98 kgfm
Locked rotor torque : 200 %
Breakdown torque : 229 %
Rated speed : 2915 rpm

Moment of inertia (J) : 0.0647 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 9 / 9Revision		
Checked by				
Date	22/10/2024			