

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11431667

Frame : 284/6T	Cooling method : IC411 - TEFC
Insulation class : F	Mounting : F-1
Duty cycle : Cont.(S1)	Rotation ¹ : Both (CW and CCW)
Ambient temperature : -20°C to +40°C	Starting method : Direct On Line
Altitude : 1000 m.a.s.l.	Approx. weight ³ : 199 kg
Protection degree : IP56	Moment of inertia (J) : 0.2467 kgm ²
Design : B	

Output [HP]	30	30	30	30
Poles	4	4	4	4
Frequency [Hz]	60	50	50	50
Rated voltage [V]	460	380	400	415
Rated current [A]	35.1	43.1	41.1	39.7
L. R. Amperes [A]	214	228	247	238
LRC [A]	6.1x(Code G)	5.3x(Code F)	6.0x(Code G)	6.0x(Code G)
No load current [A]	12.3	12.2	13.1	13.8
Rated speed [RPM]	1770	1455	1460	1465
Slip [%]	1.67	3.00	2.67	2.33
Rated torque [kgfm]	12.3	15.0	14.9	14.9
Locked rotor torque [%]	240	170	190	220
Breakdown torque [%]	240	200	220	250
Service factor	1.25	1.00	1.00	1.00
Temperature rise	80 K	105 K	105 K	105 K
Locked rotor time	36s (cold) 20s (hot)	23s (cold) 13s (hot)	23s (cold) 13s (hot)	21s (cold) 12s (hot)
Noise level ²	63.0 dB(A)	61.0 dB(A)	61.0 dB(A)	61.0 dB(A)
Efficiency (%)	25%			
	50%	93.0	90.0	90.5
	75%	93.0	90.2	91.0
	100%	93.6	90.2	91.0
Power Factor	25%			
	50%	0.70	0.76	0.73
	75%	0.80	0.83	0.82
	100%	0.84	0.86	0.85

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	6.8	6.8	6.8	6.8
	P2 (0,5;1,0)	5.8	5.8	5.8	5.8
	P3 (0,25;1,0)	5.2	5.2	5.2	5.2
	P4 (0,9;0,5)	3.1	3.1	3.1	3.1
	P5 (0,5;0,5)	2.2	2.2	2.2	2.2
	P6 (0,5;0,25)	1.4	1.4	1.4	1.4
	P7 (0,25;0,25)	0.9	0.9	0.9	0.9

	<u>Drive end</u>	<u>Non drive end</u>	Foundation loads
Bearing type :	6311 C3	6211 C3	Max. traction : 432 kgf
Sealing :	Inpro/Seal	Inpro/Seal	Max. compression : 631 kgf
Lubrication interval :	20000 h	20000 h	
Lubricant amount :	18 g	11 g	
Lubricant type :	Mobil Polyrex EM		

This revision replaces and cancel the previous one, which must be eliminated.
 (1) Looking the motor from the shaft end.
 (2) Measured at 1m and with tolerance of +3dB(A).
 (3) Approximate weight subject to changes after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	22/10/2024			

Page 1 / 6
Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Notes

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 6	Revision
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11431667



Performance : 460 V 60 Hz 4P

Rated current : 35.1 A
LRC : 6.1
Rated torque : 12.3 kgfm
Locked rotor torque : 240 %
Breakdown torque : 240 %
Rated speed : 1770 rpm

Moment of inertia (J) : 0.2467 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 6Revision		
Checked by				
Date	22/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11431667



Performance : 380 V 50 Hz 4P IE1

Rated current : 43.1 A
LRC : 5.3
Rated torque : 15.0 kgfm
Locked rotor torque : 170 %
Breakdown torque : 200 %
Rated speed : 1455 rpm

Moment of inertia (J) : 0.2467 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 6	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11431667



Performance : 400 V 50 Hz 4P IE1

Rated current : 41.1 A
LRC : 6.0
Rated torque : 14.9 kgfm
Locked rotor torque : 190 %
Breakdown torque : 220 %
Rated speed : 1460 rpm

Moment of inertia (J) : 0.2467 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 5 / 6	Revision
Checked by					
Date	22/10/2024				


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11431667



Performance : 415 V 50 Hz 4P IE2

Rated current	: 39.7 A	Moment of inertia (J)	: 0.2467 kgm ²
LRC	: 6.0	Duty cycle	: Cont.(S1)
Rated torque	: 14.9 kgfm	Insulation class	: F
Locked rotor torque	: 220 %	Service factor	: 1.00
Breakdown torque	: 250 %	Temperature rise	: 105 K
Rated speed	: 1465 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 6 / 6 Revision			
Checked by					
Date	22/10/2024				