

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11943358

Frame	: 364/5T	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 423 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.9448 kgm ²
Design	: B		

Output [HP]	60	50	50	50	60	60	60
Poles	4	4	4	4	4	4	4
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	460	380	400	415	380	400	415
Rated current [A]	71.6	71.0	69.1	67.4	86.5	82.6	80.2
L. R. Amperes [A]	444	447	477	499	450	479	497
LRC [A]	6.2x(Code G)	6.3x(Code G)	6.9x(Code H)	7.4x(Code J)	5.2x(Code E)	5.8x(Code F)	6.2x(Code G)
No load current [A]	28.0	27.6	29.8	31.6	27.6	29.8	31.6
Rated speed [RPM]	1780	1480	1482	1484	1470	1475	1477
Slip [%]	1.11	1.33	1.20	1.07	2.00	1.67	1.53
Rated torque [kgfm]	24.5	24.5	24.5	24.5	29.6	29.5	29.5
Locked rotor torque [%]	220	200	220	240	160	180	200
Breakdown torque [%]	240	240	260	280	200	210	229
Service factor	1.25	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	27s (cold) 15s (hot)	18s (cold) 10s (hot)	18s (cold) 10s (hot)	18s (cold) 10s (hot)	18s (cold) 10s (hot)	18s (cold) 10s (hot)	18s (cold) 10s (hot)
Noise level ²	67.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)	63.0 dB(A)
Efficiency (%)	25%						
	50%	94.1	93.7	93.3	93.4	94.1	94.1
	75%	94.5	93.9	93.9	94.2	93.6	94.1
	100%	95.0	94.2	94.2	94.3	93.0	94.1
Power Factor	25%						
	50%	0.71	0.71	0.68	0.65	0.76	0.70
	75%	0.80	0.80	0.78	0.76	0.82	0.80
	100%	0.83	0.84	0.82	0.81	0.85	0.83

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	5.1	5.1	5.1	5.1	5.1	5.1
	P2 (0,5;1,0)	4.1	4.1	4.1	4.1	4.1	4.1
	P3 (0,25;1,0)	3.8	3.8	3.8	3.8	3.8	3.8
	P4 (0,9;0,5)	2.6	2.6	2.6	2.6	2.6	2.6
	P5 (0,5;0,5)	1.7	1.7	1.7	1.7	1.7	1.7
	P6 (0,5;0,25)	1.2	1.2	1.2	1.2	1.2	1.2
	P7 (0,25;0,25)	0.8	0.8	0.8	0.8	0.8	0.8

Bearing type	: 6314 C3	Non drive end	6314 C3	Foundation loads	
Sealing	: Taconite		Taconite	Max. traction	: 550 kgf
	: Labyrinth		Labyrinth	Max. compression	: 973 kgf
Lubrication interval	: 12000 h		12000 h		
Lubricant amount	: 27 g		27 g		
Lubricant type	: Mobil Polyrex EM				

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	22/10/2024		Page 1 / 9	Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 9		Revision
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943358



Performance : 460 V 60 Hz 4P

Rated current : 71.6 A
LRC : 6.2
Rated torque : 24.5 kgfm
Locked rotor torque : 220 %
Breakdown torque : 240 %
Rated speed : 1780 rpm

Moment of inertia (J) : 0.9448 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 9Revision		
Checked by				
Date	22/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943358



Performance : 380 V 50 Hz 4P IE3

Rated current : 71.0 A
LRC : 6.3
Rated torque : 24.5 kgfm
Locked rotor torque : 200 %
Breakdown torque : 240 %
Rated speed : 1480 rpm

Moment of inertia (J) : 0.9448 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943358



Performance : 400 V 50 Hz 4P IE3

Rated current : 69.1 A
LRC : 6.9
Rated torque : 24.5 kgfm
Locked rotor torque : 220 %
Breakdown torque : 260 %
Rated speed : 1482 rpm

Moment of inertia (J) : 0.9448 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	22/10/2024			

Page
5 / 9

Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11943358

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 4P IE3

Rated current	: 67.4 A	Moment of inertia (J)	: 0.9448 kgm ²
LRC	: 7.4	Duty cycle	: Cont.(S1)
Rated torque	: 24.5 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	: 1.00
Breakdown torque	: 280 %	Temperature rise	: 80 K
Rated speed	: 1484 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 6 / 9 Revision			
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943358



Performance : 380 V 50 Hz 4P IE1

Rated current : 86.5 A
LRC : 5.2
Rated torque : 29.6 kgfm
Locked rotor torque : 160 %
Breakdown torque : 200 %
Rated speed : 1470 rpm

Moment of inertia (J) : 0.9448 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 7 / 9Revision		
Checked by				
Date	22/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11943358

LOAD PERFORMANCE CURVE



Performance : 400 V 50 Hz 4P IE2

Rated current	: 82.6 A	Moment of inertia (J)	: 0.9448 kgm ²
LRC	: 5.8	Duty cycle	: Cont.(S1)
Rated torque	: 29.5 kgfm	Insulation class	: F
Locked rotor torque	: 180 %	Service factor	: 1.00
Breakdown torque	: 210 %	Temperature rise	: 105 K
Rated speed	: 1475 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 8 / 9Revision			
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943358



Performance : 415 V 50 Hz 4P IE2

Rated current : 80.2 A
LRC : 6.2
Rated torque : 29.5 kgfm
Locked rotor torque : 200 %
Breakdown torque : 229 %
Rated speed : 1477 rpm

Moment of inertia (J) : 0.9448 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 9 / 9	Revision
Checked by					
Date	22/10/2024				