

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 13585407

Frame	: 444/5T	Locked rotor time	: 32s (cold) 18s (hot)
Output	: 75 HP (55 kW)	Temperature rise	: 80 K
Poles	: 8	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 74.7 A	Protection degree	: IP56
L. R. Amperes	: 478 A	Cooling method	: IC411 - TEFC
LRC	: 6.4x(Code H)	Mounting	: F-1
No load current	: 32.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 890 rpm	Noise level ²	: 63.0 dB(A)
Slip	: 1.11 %	Starting method	: Direct On Line
Rated torque	: 61.2 kgfm	Approx. weight ³	: 680 kg
Locked rotor torque	: 170 %		
Breakdown torque	: 200 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 3.10 kgm ²		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	93.0	93.6	93.6	Max. traction	: 730 kgf
Power Factor	0.64	0.74	0.79	Max. compression	: 1410 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
6.6	5.2	4.7	3.3	2.2	1.5	1.0

	Drive end	Non drive end
Bearing type	: 6319 C3	6316 C3
Sealing	: Inpro/Seal	Inpro/Seal
Lubrication interval	: 17000 h	20000 h
Lubricant amount	: 45 g	34 g
Lubricant type	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	23/10/2024		Page 1 / 2	Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 13585407



Performance : 575 V 60 Hz 8P

Rated current : 74.7 A
LRC : 6.4
Rated torque : 61.2 kgfm
Locked rotor torque : 170 %
Breakdown torque : 200 %
Rated speed : 890 rpm

Moment of inertia (J) : 3.10 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date					