

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W21 In Line Extra Thrust Premium Product code : 12465079
Efficiency Three-Phase

Frame	: 444/5LP	Locked rotor time	: 32s (cold) 18s (hot)
Output	: 125 HP	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 110 A	Protection degree	: IP55
L. R. Amperes	: 704 A	Cooling method	: IC411 - TEFC
LRC	: 6.4x(Code G)	Mounting	: W-6
No load current	: 37.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1785 rpm	Noise level ²	: 76.0 dB(A)
Slip	: 0.83 %	Starting method	: Direct On Line
Rated torque	: 50.8 kgfm	Approx. weight ³	: 833 kg
Locked rotor torque	: 200 %		
Breakdown torque	: 220 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 2.41 kgm ²		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads
Efficiency (%)	0.000	95.0	95.4	95.4	Max. traction
Power Factor	0.00	0.76	0.83	0.86	Max. compression

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6314	7315BECB
Sealing	:	Oil Seal	Lip Seal
Lubrication interval	:	4895 h	3268 h
Lubricant amount	:	27 g	30 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		1 / 2		
Date	24/10/2024			


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : W21 In Line Extra Thrust Premium Efficiency Three-Phase Product code : 12465079



Performance : 575 V 60 Hz 4P

Rated current : 110 A	Moment of inertia (J) : 2.41 kgm ²
LRC : 6.4	Duty cycle : Cont.(S1)
Rated torque : 50.8 kgfm	Insulation class : F
Locked rotor torque : 200 %	Service factor : 1.15
Breakdown torque : 220 %	Temperature rise : 80 K
Rated speed : 1785 rpm	Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	24/10/2024			