

# DATA SHEET

## Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : General Single-Phase Product code : 10722428

Frame	: F143/5T	Locked rotor time	: 10s (cold) 6s (hot)
Output	: 1 HP (0.75 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 115/208-230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 12.8/6.40-6.40 A	Protection degree	: IP55
L. R. Amperes	: 89.6/44.8-44.8 A	Cooling method	: IC411 - TEFC
LRC	: 7.0x(Code M)	Mounting	: F-1
No load current	: 9.00/3.88-4.50 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 3500 rpm	Starting method	: Direct On Line
Slip	: 2.78 %	Approx. weight <sup>3</sup>	: 16.4 kg
Rated torque	: 0.207 kgfm		
Locked rotor torque	: 320 %		
Breakdown torque	: 280 %		
Insulation class	: B		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0022 kgm <sup>2</sup>		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	55.0	63.0	67.0	Max. traction	: 8 kgf
Power Factor	0.56	0.67	0.75	Max. compression	: 24 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6205 ZZ	6203 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

### Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	26/10/2024				
		Page		Revision	
		1 / 2			

# LOAD PERFORMANCE CURVE

Single Phase Induction Motor - Squirrel Cage




Customer :

Product line : General Single-Phase

Product code : 10722428

LOAD PERFORMANCE CURVE



Performance : 115/208-230 V 60 Hz 2P

Rated current : 12.8/6.40-6.40 A  
LRC : 7.0  
Rated torque : 0.207 kgfm  
Locked rotor torque : 320 %  
Breakdown torque : 280 %  
Rated speed : 3500 rpm

Moment of inertia (J) : 0.0022 kgm<sup>2</sup>  
Duty cycle : Cont.(S1)  
Insulation class : B  
Service factor :  
Temperature rise : 80 K

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date					