

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12744550

Frame	: 182/4T	Locked rotor time	: 30s (cold) 17s (hot)
Output	: 1.5 HP (1.1 kW)	Temperature rise	: 80 K
Poles	: 8	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 2.27 A	Protection degree	: IP55
L. R. Amperes	: 13.4 A	Cooling method	: IC411 - TEFC
LRC	: 5.9x(Code L)	Mounting	: F-1
No load current	: 1.68 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 860 rpm	Noise level ²	: 50.0 dB(A)
Slip	: 4.44 %	Starting method	: Direct On Line
Rated torque	: 1.25 kgfm	Approx. weight ³	: 35.4 kg
Locked rotor torque	: 229 %		
Breakdown torque	: 290 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0243 kgm ²		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	76.0	78.0	78.5	Max. traction	: 59 kgf
Power Factor	0.43	0.54	0.62	Max. compression	: 94 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
25.9	20.5	18.6	18.4	13.2	11.6	8.8

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6207 ZZ	6206 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 2		
Checked by				
Date	27/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12744550

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 8P			
Rated current	: 2.27 A	Moment of inertia (J)	: 0.0243 kgm ²
LRC	: 5.9	Duty cycle	: Cont.(S1)
Rated torque	: 1.25 kgfm	Insulation class	: F
Locked rotor torque	: 229 %	Service factor	: 1.25
Breakdown torque	: 290 %	Temperature rise	: 80 K
Rated speed	: 860 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2	Revision
Checked by					
Date	27/10/2024				