

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11431671

Frame	: 364/5TS	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 383 kg
Protection degree	: IP56	Moment of inertia (J)	: 0.4485 kgm ²
Design	: B		

Output [HP]	60	50	50	50	60	60	60
Poles	2	2	2	2	2	2	2
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	460	380	400	415	380	400	415
Rated current [A]	67.0	66.6	63.7	62.1	81.3	77.6	74.8
L. R. Amperes [A]	429	406	433	447	407	435	449
LRC [A]	6.4x(Code G)	6.1x(Code F)	6.8x(Code G)	7.2x(Code H)	5.0x(Code D)	5.6x(Code F)	6.0x(Code F)
No load current [A]	15.0	15.0	16.2	17.4	15.0	16.2	17.4
Rated speed [RPM]	3550	2945	2950	2955	2935	2940	2945
Slip [%]	1.39	1.83	1.67	1.50	2.17	2.00	1.83
Rated torque [kgfm]	12.3	12.3	12.3	12.3	14.8	14.8	14.8
Locked rotor torque [%]	190	180	210	220	150	170	180
Breakdown torque [%]	250	240	270	290	200	220	240
Service factor	1.25	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	25s (cold) 14s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)	21s (cold) 12s (hot)
Noise level ²	79.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)
Efficiency (%)	25%						
	50%	91.7	92.1	91.7	91.6	92.4	92.4
	75%	93.0	92.8	92.8	92.9	93.0	93.0
	100%	93.6	92.8	93.1	93.1	92.4	93.0
Power Factor	25%						
	50%	0.81	0.81	0.79	0.76	0.85	0.83
	75%	0.88	0.88	0.87	0.85	0.90	0.89
	100%	0.90	0.91	0.90	0.89	0.91	0.90

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	7.4	8.4	8.0	8.0	8.9	8.2	8.2
	P2 (0,5;1,0)	5.8	6.8	6.4	6.4	7.3	6.5	6.5
	P3 (0,25;1,0)	5.1	6.1	5.7	5.7	6.5	5.8	5.8
	P4 (0,9;0,5)	3.7	4.1	4.0	4.0	4.4	4.0	4.0
	P5 (0,5;0,5)	2.3	2.6	2.5	2.5	2.8	2.5	2.5
	P6 (0,5;0,25)	1.4	1.7	1.6	1.6	1.8	1.6	1.6
	P7 (0,25;0,25)	0.9	1.1	1.0	1.0	1.2	1.0	1.0

Bearing type	Drive end	Non drive end	Foundation loads
	: 6314 C3	: 6314 C3	
	Sealing	Inpro/Seal	
	: Inpro/Seal	: Inpro/Seal	
	Lubrication interval	: 4000 h	
Lubricant amount	: 27 g	: 27 g	Max. traction : 206 kgf
	Lubricant type	: Mobil Polyrex EM	
			Max. compression : 590 kgf

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 1 / 9	Revision
Checked by					
Date	27/10/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 9		Revision
Checked by					
Date	27/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11431671



Performance : 460 V 60 Hz 2P

Rated current : 67.0 A
LRC : 6.4
Rated torque : 12.3 kgfm
Locked rotor torque : 190 %
Breakdown torque : 250 %
Rated speed : 3550 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 9Revision		
Checked by				
Date	27/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11431671

LOAD PERFORMANCE CURVE



Performance : 380 V 50 Hz 2P IE2			
Rated current	: 66.6 A	Moment of inertia (J)	: 0.4485 kgm ²
LRC	: 6.1	Duty cycle	: Cont.(S1)
Rated torque	: 12.3 kgfm	Insulation class	: F
Locked rotor torque	: 180 %	Service factor	: 1.00
Breakdown torque	: 240 %	Temperature rise	: 80 K
Rated speed	: 2945 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 4 / 9	Revision
Checked by					
Date	27/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11431671



Performance : 400 V 50 Hz 2P IE2

Rated current : 63.7 A
LRC : 6.8
Rated torque : 12.3 kgfm
Locked rotor torque : 210 %
Breakdown torque : 270 %
Rated speed : 2950 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 9Revision		
Checked by				
Date	27/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11431671

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 2P IE2			
Rated current	: 62.1 A	Moment of inertia (J)	: 0.4485 kgm ²
LRC	: 7.2	Duty cycle	: Cont.(S1)
Rated torque	: 12.3 kgfm	Insulation class	: F
Locked rotor torque	: 220 %	Service factor	: 1.00
Breakdown torque	: 290 %	Temperature rise	: 80 K
Rated speed	: 2955 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 6 / 9	Revision
Checked by					
Date	27/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11431671



Performance : 380 V 50 Hz 2P IE1

Rated current : 81.3 A
LRC : 5.0
Rated torque : 14.8 kgfm
Locked rotor torque : 150 %
Breakdown torque : 200 %
Rated speed : 2935 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 7 / 9Revision		
Checked by				
Date	27/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11431671

LOAD PERFORMANCE CURVE



Performance : 400 V 50 Hz 2P IE2

Rated current	: 77.6 A	Moment of inertia (J)	: 0.4485 kgm ²
LRC	: 5.6	Duty cycle	: Cont.(S1)
Rated torque	: 14.8 kgfm	Insulation class	: F
Locked rotor torque	: 170 %	Service factor	: 1.00
Breakdown torque	: 220 %	Temperature rise	: 105 K
Rated speed	: 2940 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 8 / 9 Revision			
Checked by					
Date	27/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11431671



Performance : 415 V 50 Hz 2P IE2

Rated current : 74.8 A
LRC : 6.0
Rated torque : 14.8 kgfm
Locked rotor torque : 180 %
Breakdown torque : 240 %
Rated speed : 2945 rpm

Moment of inertia (J) : 0.4485 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	27/10/2024			

Page 9 / 9
Revision