

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium Efficiency Three-Phase Product code : 15946558

Frame	: 449T	Locked rotor time	: 25s (cold) 14s (hot)
Output	: 350 HP (260 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 323 A	Protection degree	: IP55
L. R. Amperes	: 2650 A	Cooling method	: IC411 - TEFC
LRC	: 8.2x(Code J)	Mounting	: F-1
No load current	: 122 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1785 rpm	Noise level ²	: 80.0 dB(A)
Slip	: 0.83 %	Starting method	: Direct On Line
Rated torque	: 142 kgfm	Approx. weight ³	: 1492 kg
Locked rotor torque	: 280 %		
Breakdown torque	: 290 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 4.98 kgm ²		
Design	: A		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	95.4	95.8	96.2	Max. traction	: 2864 kgf
Power Factor	0.70	0.80	0.84	Max. compression	: 4356 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6322 C3	6319 C3
Sealing	:	Viton Oil Seal	Viton Seal
Lubrication interval	:	5138 h	7038 h
Lubricant amount	:	60 g	45 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3 Revision		
Checked by				
Date	30/10/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 3Revision	
Checked by					
Date	30/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA
Premium Efficiency Three-Phase

Product code : 15946558



Performance : 575 V 60 Hz 4P

Rated current	: 323 A	Moment of inertia (J)	: 4.98 kgm ²
LRC	: 8.2	Duty cycle	: Cont.(S1)
Rated torque	: 142 kgfm	Insulation class	: F
Locked rotor torque	: 280 %	Service factor	: 1.15
Breakdown torque	: 290 %	Temperature rise	: 80 K
Rated speed	: 1785 rpm	Design	: A

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 3		
Checked by				
Date	30/10/2024			
		Revision		