

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 P Base NEMA Premium Efficiency Three-Phase Product code : 13128897

Frame : 184HP	Cooling method : IC411 - TEFC
Insulation class : F	Mounting : W-6
Duty cycle : Cont.(S1)	Rotation ¹ : Both (CW and CCW)
Ambient temperature : -20°C to +40°C	Starting method : Direct On Line
Altitude : 1000 m.a.s.l.	Approx. weight ³ : 47.3 kg
Protection degree : IP55	Moment of inertia (J) : 0.0094 kgm ²
Design : B	

Output [HP]	5	4	4	4	5	5	5
Poles	2	2	2	2	2	2	2
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	11.8/5.90	5.85	5.57	5.43	7.14	6.78	6.61
L. R. Amperes [A]	89.7/44.8	43.9	46.2	50.5	42.8	46.1	49.6
LRC [A]	7.6x(Code J)	7.5x(Code J)	8.3x(Code K)	9.3x(Code L)	6.0x(Code G)	6.8x(Code H)	7.5x(Code J)
No load current [A]	4.00/2.00	2.00	2.15	2.25	2.00	2.15	2.25
Rated speed [RPM]	3500	2900	2915	2920	2855	2880	2890
Slip [%]	2.78	3.33	2.83	2.67	4.83	4.00	3.67
Rated torque [kgfm]	1.04	1.00	0.996	0.994	1.27	1.26	1.26
Locked rotor torque [%]	229	220	250	270	180	210	220
Breakdown torque [%]	350	310	350	380	240	270	300
Service factor	1.25	1.25	1.25	1.25	1.25	1.25	1.25
Temperature rise	80 K	80 K	80 K	80 K	80 K	80 K	80 K
Locked rotor time	32s (cold) 18s (hot)	32s (cold) 18s (hot)	32s (cold) 18s (hot)	28s (cold) 16s (hot)	25s (cold) 14s (hot)	25s (cold) 14s (hot)	23s (cold) 13s (hot)
Noise level ²	66.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)	62.0 dB(A)
Efficiency (%)	25%	0.000			0.000		
	50%	86.5	86.3	86.3	86.1	87.5	87.5
	75%	88.5	87.7	88.2	88.2	87.5	88.5
	100%	88.5	87.5	88.3	88.3	86.5	87.5
Power Factor	25%	0.00			0.00		
	50%	0.76	0.74	0.71	0.68	0.81	0.76
	75%	0.85	0.85	0.83	0.81	0.88	0.87
	100%	0.89	0.89	0.88	0.87	0.91	0.89

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	12.2	13.4	12.4	12.4	14.7	13.4	13.4
	P2 (0,5;1,0)	10.1	11.1	10.3	10.3	12.1	11.1	11.1
	P3 (0,25;1,0)	9.7	10.7	9.9	9.9	11.7	10.7	10.7
	P4 (0,9;0,5)	5.9	6.5	6.1	6.1	7.1	6.5	6.5
	P5 (0,5;0,5)	3.7	4.0	3.7	3.7	4.4	4.0	4.0
	P6 (0,5;0,25)	2.3	2.5	2.3	2.3	2.7	2.5	2.5
	P7 (0,25;0,25)	1.5	1.6	1.5	1.5	1.8	1.6	1.6

Bearing type	: 6308 ZZ	Non drive end 6206 ZZ	Foundation loads
Sealing	: V'Ring	V'Ring	Max. traction
Lubrication interval	: -	-	Max. compression
Lubricant amount	: -	-	
Lubricant type	: Mobil Polyrex EM		

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/10/2024		Page 1 / 9	Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Notes
USABLE @208V 13.1A SF 1.15 SFA 15.0A

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 9		Revision
Checked by					
Date	29/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 P Base NEMA Premium
Efficiency Three-Phase

Product code : 13128897



Performance : 230/460 V 60 Hz 2P

Rated current : 11.8/5.90 A
LRC : 7.6
Rated torque : 1.04 kgfm
Locked rotor torque : 229 %
Breakdown torque : 350 %
Rated speed : 3500 rpm

Moment of inertia (J) : 0.0094 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				3 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 P Base NEMA Premium
Efficiency Three-Phase

Product code : 13128897



Performance : 380 V 50 Hz 2P IE3

Rated current : 5.85 A
LRC : 7.5
Rated torque : 1.00 kgfm
Locked rotor torque : 220 %
Breakdown torque : 310 %
Rated speed : 2900 rpm

Moment of inertia (J) : 0.0094 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 P Base NEMA Premium
Efficiency Three-Phase

Product code : 13128897



Performance : 400 V 50 Hz 2P IE3

Rated current : 5.57 A
LRC : 8.3
Rated torque : 0.996 kgfm
Locked rotor torque : 250 %
Breakdown torque : 350 %
Rated speed : 2915 rpm

Moment of inertia (J) : 0.0094 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 9Revision		
Checked by				
Date	29/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 P Base NEMA Premium Product code : 13128897
Efficiency Three-Phase

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 2P IE3

Rated current	: 5.43 A	Moment of inertia (J)	: 0.0094 kgm ²
LRC	: 9.3	Duty cycle	: Cont.(S1)
Rated torque	: 0.994 kgfm	Insulation class	: F
Locked rotor torque	: 270 %	Service factor	: 1.25
Breakdown torque	: 380 %	Temperature rise	: 80 K
Rated speed	: 2920 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 6 / 9 Revision			
Checked by					
Date	29/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 P Base NEMA Premium
Efficiency Three-Phase

Product code : 13128897



Performance : 380 V 50 Hz 2P IE2

Rated current : 7.14 A
LRC : 6.0
Rated torque : 1.27 kgfm
Locked rotor torque : 180 %
Breakdown torque : 240 %
Rated speed : 2855 rpm

Moment of inertia (J) : 0.0094 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 7 / 9	Revision
Checked by					
Date	29/10/2024				


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 P Base NEMA Premium Product code : 13128897
Efficiency Three-Phase



Performance : 400 V 50 Hz 2P IE2

Rated current	: 6.78 A	Moment of inertia (J)	: 0.0094 kgm ²
LRC	: 6.8	Duty cycle	: Cont.(S1)
Rated torque	: 1.26 kgfm	Insulation class	: F
Locked rotor torque	: 210 %	Service factor	: 1.25
Breakdown torque	: 270 %	Temperature rise	: 80 K
Rated speed	: 2880 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 8 / 9 Revision			
Checked by					
Date	29/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 P Base NEMA Premium
Efficiency Three-Phase

Product code : 13128897



Performance : 415 V 50 Hz 2P IE2

Rated current : 6.61 A
LRC : 7.5
Rated torque : 1.26 kgfm
Locked rotor torque : 220 %
Breakdown torque : 300 %
Rated speed : 2890 rpm

Moment of inertia (J) : 0.0094 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 9 / 9	Revision
Checked by					
Date	29/10/2024				

