

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12448182

Frame	: 324/6TSC	Locked rotor time	: 39s (cold) 22s (hot)
Output	: 40 HP (30 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 37.0 A	Protection degree	: IP55
L. R. Amperes	: 233 A	Cooling method	: IC411 - TEFC
LRC	: 6.3x(Code G)	Mounting	: F-1
No load current	: 10.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3555 rpm	Noise level ²	: 76.0 dB(A)
Slip	: 1.25 %	Starting method	: Direct On Line
Rated torque	: 8.15 kgfm	Approx. weight ³	: 226 kg
Locked rotor torque	: 250 %		
Breakdown torque	: 240 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.2063 kgm ²		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	0.000	91.7	92.4	92.4	Max. traction	: 133 kgf
Power Factor	0.00	0.80	0.86	0.88	Max. compression	: 359 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
7.4	4.7	3.8	4.6	2.2	1.7	0.8

	Drive end	Non drive end
Bearing type	: 6312 C3	6212 C3
Sealing	: V'Ring	V'Ring
Lubrication interval	: 12000 h	15000 h
Lubricant amount	: 21 g	13 g
Lubricant type	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	19/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12448182



Performance : 575 V 60 Hz 2P

Rated current : 37.0 A
LRC : 6.3
Rated torque : 8.15 kgfm
Locked rotor torque : 250 %
Breakdown torque : 240 %
Rated speed : 3555 rpm

Moment of inertia (J) : 0.2063 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 2	Revision
Checked by					
Date	19/10/2024				

