

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line		: Saw Arbor Motor Standard Efficiency Three-Phase		Product code : 14984959		
Frame	:	80S/MS	Locked rotor time	: 16s (cold) 9s (hot)		
Output	:	3 HP (2.2 kW)	Temperature rise	: 80 K		
Poles	:	2	Duty cycle	: S6		
Frequency	:	60 Hz	Ambient temperature	: -20°C to +40°C		
Rated voltage	:	208-230/460 V	Altitude	: 1000 m.a.s.l.		
Rated current	:	9.49-8.58/4.29 A	Protection degree	: IP54		
L. R. Amperes	:	69.3-62.6/31.3 A	Cooling method	: IC411 - TEFC		
LRC	:	7.3	Mounting	: B3R(D)		
No load current	:	4.55-4.11/2.06 A	Rotation <sup>1</sup>	: CW		
Rated speed	:	3500 rpm	Noise level <sup>2</sup>	: 62.0 dB(A)		
Slip	:	2.78 %	Starting method	: Direct On Line		
Rated torque	:	0.622 kgfm	Approx. weight <sup>3</sup>	: 38.6 kg		
Locked rotor torque	:	330 %				
Breakdown torque	:	370 %				
Insulation class	:	F				
Service factor	:	1.15				
Moment of inertia (J)	:	0.0032 kgm <sup>2</sup>				
Design	:	N				
Output	50%	75%	100%	Foundation loads		
Efficiency (%)	76.0	79.5	80.5	Max. traction : 29 kgf		
Power Factor	0.65	0.75	0.80	Max. compression : 67 kgf		
		<u>Drive end</u>		<u>Non drive end</u>		
Bearing type	:	6307 ZZ		6207 ZZ		
Sealing	:	Without Bearing Seal		Without Bearing Seal		
Lubrication interval	:	-		-		
Lubricant amount	:	-		-		
Lubricant type	:	Mobil Polyrex EM				
Notes						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	29/10/2024				1 / 2	

# LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : Saw Arbor Motor Standard  
Efficiency Three-Phase

Product code : 14984959

LOAD PERFORMANCE CURVE



Performance : 208-230/460 V 60 Hz 2P

Rated current : 9.49-8.58/4.29 A  
LRC : 7.3  
Rated torque : 0.622 kgfm  
Locked rotor torque : 330 %  
Breakdown torque : 370 %  
Rated speed : 3500 rpm

Moment of inertia (J) : 0.0032 kgm<sup>2</sup>  
Duty cycle : S6  
Insulation class : F  
Service factor : 1.15  
Temperature rise : 80 K  
Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	29/10/2024			

