DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : Premium Efficiency Three-Phase Product code : 15065846

Frame	: W56	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation[1]	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight[3]	: 7.2 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.0006 kgm²

Output [HP]		0.33	0.33	0.33
Poles		2	2	2
Frequency [Hz]		60	50	50
Rated voltage [V]		208-230/460	190-220/380	415
Rated current [A]		1.30-1.15/0.573	1.29-1.12/0.646	0.624
L. R. Amperes [A]		9.27-8.14/4.07	7.24-6.25/3.62	3.93
LRC [A]		7.1x(Code L)	5.6x(Code J)	6.3x(Code K)
No load current [A]		0.610-0.708/0.354	0.692-0.598/0.346	0.398
Rated speed [RPM]		3450	2800	2830
Slip [%]		4.17	6.67	5.67
Rated torque [kgfm]		0.069	0.086	0.085
Locked rotor torque [%]		320	240	290
Breakdown torque [%]		370	260	310
Service factor			1.15	1.15
Temperature rise		80 K	80 K	80 K
Locked rotor time		50s (cold) 28s (hot)	50s (cold) 28s (hot)	43s (cold) 24s (hot)
Noise level[2]		65.0 dB(A)	64.0 dB(A)	64.0 dB(A)
Efficiency (%)	25%			
	50%	59.5	65.8	64.3
	75%	66.0	70.6	70.2
	100%	72.0	71.7	72.4
Power Factor	25%			
	50%	0.61	0.66	0.58
	75%	0.71	0.77	0.70
	100%	0.76	0.82	0.77

		Drive end	Non drive end
Bearing type	:	6203 ZZ	6202 ZZ
Sealing	:	V'Ring	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Foundation loads
Max. traction : 4 kgf
Max. compression : 12 kgf

Notes
USABLE @208V SF 1.00

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date


Performed by				
Checked by			Page	Revision
Date	17/05/2022		1 / 4	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:		
Product line	: Premium Efficiency Three-Phase	Product code :	15065846



Performance	: 208-230/460 V 60 Hz 2P		
Rated current	: 1.30-1.15/0.573 A	Moment of inertia (J)	: 0.0006 kgm²
LRC	: 7.1	Duty cycle	: Cont.(S1)
Rated torque	: 0.069 kgfm	Insulation class	: F
Locked rotor torque	: 320 %	Service factor	:
Breakdown torque	: 370 %	Temperature rise	: 80 K
Rated speed	: 3450 rpm		

Rev.	Changes Summary	Performed	Checked	Date


Performed by				
Checked by			Page	Revision
Date	17/05/2022		2 / 4	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:		
Product line	: Premium Efficiency Three-Phase	Product code :	15065846



Performance	: 190-220/380 V 50 Hz 2P		
Rated current	: 1.29-1.12/0.646 A	Moment of inertia (J)	: 0.0006 kgm²
LRC	: 5.6	Duty cycle	: Cont.(S1)
Rated torque	: 0.086 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	: 1.15
Breakdown torque	: 260 %	Temperature rise	: 80 K
Rated speed	: 2800 rpm		

Rev.	Changes Summary	Performed	Checked	Date


Performed by				
Checked by			Page	Revision
Date	17/05/2022		3 / 4	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:		
Product line	: Premium Efficiency Three-Phase	Product code :	15065846




Performance	: 415 V 50 Hz 2P		
Rated current	: 0.624 A	Moment of inertia (J)	: 0.0006 kgm²
LRC	: 6.3	Duty cycle	: Cont.(S1)
Rated torque	: 0.085 kgfm	Insulation class	: F
Locked rotor torque	: 290 %	Service factor	: 1.15
Breakdown torque	: 310 %	Temperature rise	: 80 K
Rated speed	: 2830 rpm		


Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	17/05/2022		4 / 4	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice



DE Shaft End



- Reinforce the foot with 2 mig welding spots
- Color Munsell N 1 matte black
- Painting plan 207N
- Mounting MARKET F-1/B3R(D)
- Mounting F-1/B3R(D)

0.33 HP 02 Poles 60 Hz | A

Scale 1 : 3

ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
			HYBRISUSER				00

EXECUTED	HYBRISUSER
CHECKED	
RELEASED	
REL. DATE	

THREE PH. MOTOR ROLLED STEEL PREM. EFF.
FRAME W56 IP55 TEFC

PREVIEW
WDD 00
SHEET 1 / 1

Dimensions in inches

A3

WEG's property. Forbidden reproduction without previous authorization.