

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Cooling Tower NEMA Premium Efficiency Three-Phase Product code : 17447947

|                       |                           |                             |                        |
|-----------------------|---------------------------|-----------------------------|------------------------|
| Frame                 | : 182/4T                  | Locked rotor time           | : 27s (cold) 15s (hot) |
| Output                | : 5 HP (3.7 kW)           | Temperature rise            | : 80 K                 |
| Poles                 | : 4                       | Duty cycle                  | : Cont.(S1)            |
| Frequency             | : 60 Hz                   | Ambient temperature         | : -20°C to +40°C       |
| Rated voltage         | : 200-208 V               | Altitude                    | : 1000 m.a.s.l.        |
| Rated current         | : 14.9-14.3 A             | Protection degree           | : IP55                 |
| L. R. Amperes         | : 112-107 A               | Cooling method              | : IC411 - TEFC         |
| LRC                   | : 7.5x(Code J)            | Mounting                    | : F-1                  |
| No load current       | : 6.90-5.17 A             | Rotation <sup>1</sup>       | : Both (CW and CCW)    |
| Rated speed           | : 1750 rpm                | Noise level <sup>2</sup>    | : 56.0 dB(A)           |
| Slip                  | : 2.78 %                  | Starting method             | : Direct On Line       |
| Rated torque          | : 2.07 kgfm               | Approx. weight <sup>3</sup> | : 43.0 kg              |
| Locked rotor torque   | : 229 %                   |                             |                        |
| Breakdown torque      | : 300 %                   |                             |                        |
| Insulation class      | : F                       |                             |                        |
| Service factor        | : 1.25                    |                             |                        |
| Moment of inertia (J) | : 0.0169 kgm <sup>2</sup> |                             |                        |
| Design                | : B                       |                             |                        |

|                |       |      |      |      |                            |
|----------------|-------|------|------|------|----------------------------|
| Output         | 25%   | 50%  | 75%  | 100% | Foundation loads           |
| Efficiency (%) | 0.000 | 88.5 | 89.5 | 89.5 | Max. traction : 107 kgf    |
| Power Factor   | 0.00  | 0.60 | 0.72 | 0.80 | Max. compression : 153 kgf |

Losses at normative operating points (speed;torque), in percentage of rated output power

| P1 (0,9;1,0) | P2 (0,5;1,0) | P3 (0,25;1,0) | P4 (0,9;0,5) | P5 (0,5;0,5) | P6 (0,5;0,25) | P7 (0,25;0,25) |
|--------------|--------------|---------------|--------------|--------------|---------------|----------------|
| 11.1         | 9.3          | 9.4           | 5.6          | 3.9          | 2.7           | 1.9            |

|                      |                  |                      |
|----------------------|------------------|----------------------|
|                      | <u>Drive end</u> | <u>Non drive end</u> |
| Bearing type         | : 6207 2RS       | : 6206 2RS           |
| Sealing              | : V'Ring         | : V'Ring             |
| Lubrication interval | : -              | : -                  |
| Lubricant amount     | : -              | : -                  |
| Lubricant type       | : 00088          |                      |

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev.         | Changes Summary | Performed  | Checked | Date     |
|--------------|-----------------|------------|---------|----------|
|              |                 |            |         |          |
| Performed by |                 |            |         |          |
| Checked by   |                 |            |         |          |
| Date         | 02/07/2026      |            |         |          |
|              |                 | Page 1 / 3 |         | Revision |

Customer :

Space heater information

Voltage: 110-127/200-240 V

| Rev.         | Changes Summary |  | Performed     | Checked | Date     |
|--------------|-----------------|--|---------------|---------|----------|
|              |                 |  |               |         |          |
| Performed by |                 |  | Page<br>2 / 3 |         | Revision |
| Checked by   |                 |  |               |         |          |
| Date         | 02/07/2026      |  |               |         |          |

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Cooling Tower NEMA  
Premium Efficiency Three-Phase

Product code : 17447947



Performance : 200-208 V 60 Hz 4P

Rated current : 14.9-14.3 A  
LRC : 7.5  
Rated torque : 2.07 kgfm  
Locked rotor torque : 229 %  
Breakdown torque : 300 %  
Rated speed : 1750 rpm

Moment of inertia (J) : 0.0169 kgm<sup>2</sup>  
Duty cycle : Cont.(S1)  
Insulation class : F  
Service factor : 1.25  
Temperature rise : 80 K  
Design : B

| Rev.         | Changes Summary | Performed             | Checked | Date |
|--------------|-----------------|-----------------------|---------|------|
|              |                 |                       |         |      |
| Performed by |                 | Page<br>3 / 3Revision |         |      |
| Checked by   |                 |                       |         |      |
| Date         | 02/07/2026      |                       |         |      |

