

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Super Premium Efficiency Three-Phase Product code : 19249343

Frame	: 254/6T	Locked rotor time	: 41s (cold) 23s (hot)
Output	: 20 HP (15 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 18.4 A	Protection degree	: IP55
L. R. Amperes	: 140 A	Cooling method	: IC411 - TEFC
LRC	: 7.6x(Code H)	Mounting	: F-1
No load current	: 5.76 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3545 rpm	Noise level ²	: 72.0 dB(A)
Slip	: 1.53 %	Starting method	: Direct On Line
Rated torque	: 4.09 kgfm	Approx. weight ³	: 141 kg
Locked rotor torque	: 260 %		
Breakdown torque	: 340 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0804 kgm ²		
Design	: A		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	91.0	92.4	93.0	Max. traction	: 140 kgf
Power Factor	0.75	0.84	0.88	Max. compression	: 298 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
7.1	5.5	5.1	3.7	2.2	1.4	0.8

	Drive end	Non drive end
Bearing type	: 6309 C3	: 6209 C3
Sealing	: V'Ring	: V'Ring
Lubrication interval	: 19000 h	: 20000 h
Lubricant amount	: 13 g	: 9 g
Lubricant type	: Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	07/07/2026			
			Page	Revision
			1 / 2	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Super Premium Efficiency
Three-Phase

Product code : 19249343



Performance : 575 V 60 Hz 2P

Rated current : 18.4 A
LRC : 7.6
Rated torque : 4.09 kgfm
Locked rotor torque : 260 %
Breakdown torque : 340 %
Rated speed : 3545 rpm

Moment of inertia (J) : 0.0804 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : A

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 2Revision		
Checked by				
Date	07/07/2026			

