

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer	:				
Product line	: NEMA Premium Efficiency Three-Phase	Product code :	12630643		
Frame	: 182/4T	Cooling method	: IC01 - ODP		
Insulation class	: F	Mounting	: F-1		
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)		
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line		
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 36.8 kg		
Design	: B	Moment of inertia (J)	: 0.0169 kgm ²		
Output [HP]	5				
Poles	4				
Frequency [Hz]	60				
Rated voltage [V]	575				
Rated current [A]	5.06				
L. R. Amperes [A]	36.5				
LRC [A]	7.2x(Code J)				
No load current [A]	2.52				
Rated speed [RPM]	1760				
Slip [%]	2.22				
Rated torque [kgfm]	2.06				
Locked rotor torque [%]	200				
Breakdown torque [%]	310				
Service factor	1.15				
Temperature rise	80 K				
Locked rotor time	21s (cold) 12s (hot)				
Noise level ²	55.0 dB(A)				
Efficiency (%)	25%	87.5			
	50%	88.5			
	75%	88.5			
	100%	89.5			
Power Factor	25%	0.38			
	50%	0.63			
	75%	0.76			
	100%	0.82			
Bearing type	: Drive end	Non drive end	Foundation loads		
Sealing	: Without	Without	Max. traction	: 115 kgf	
Lubrication interval	: -	-	Max. compression	: 152 kgf	
Lubricant amount	: -	-			
Lubricant type	: Mobil Polyrex EM				
Notes					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	13/05/2022			1 / 2	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : NEMA Premium Efficiency Three-Phase Product code : 12630643

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 4P

Rated current	: 5.06 A	Moment of inertia (J)	: 0.0169 kgm ²
LRC	: 7.2	Duty cycle	: Cont.(S1)
Rated torque	: 2.06 kgfm	Insulation class	: F
Locked rotor torque	: 200 %	Service factor	: 1.15
Breakdown torque	: 310 %	Temperature rise	: 80 K
Rated speed	: 1760 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

