

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - ODP - Nema Premium Efficiency

Product code : 12792536

|                       |                   |                             |                          |
|-----------------------|-------------------|-----------------------------|--------------------------|
| Frame                 | : 182/4T          | Locked rotor time           | : 12 s (hot) 22 s (cold) |
| Output                | : 5 HP (3.7 kW)   | Temperature rise            | : 80 K                   |
| Poles                 | : 4               | Duty cycle                  | : S1                     |
| Frequency             | : 60 Hz           | Ambient temperature         | : -20 °C to +40 °C       |
| Rated voltage         | : 575 V           | Altitude                    | : 3280 ft                |
| Rated current         | : 5.06 A          | Protection degree           | : IP21                   |
| L. R. Amperes         | : 36.5 A          | Cooling method              | : IC01 - ODP             |
| LRC                   | : 7.2             | Mounting                    | : F-1/B3R(D)             |
| No load current       | : 2.52 A          | Rotation <sup>1</sup>       | : Both                   |
| Rated speed           | : 1760 rpm        | Noise level <sup>2</sup>    | : 55.0 dB(A)             |
| Slip                  | : 2.22 %          | Vibration class             | : A                      |
| Rated torque          | : 14.7 ft.lb      | Starting method             | : Direct On Line         |
| Locked rotor torque   | : 200 %           | Approx. weight <sup>3</sup> | : 79.8 lb                |
| Pull up torque        | : 170 %           | Painting plan               | : 207N                   |
| Breakdown torque      | : 310 %           | Color                       | : MUNSELL N 1 - MATTE    |
| Insulation class      | : F               | Design                      | : B                      |
| Service factor        | : 1.15            |                             |                          |
| Moment of inertia (J) | : 0.4010 sq.ft.lb |                             |                          |

|                |      |      |      |
|----------------|------|------|------|
| Output         | 50%  | 75%  | 100% |
| Efficiency (%) | 88.5 | 88.5 | 89.5 |
| Power Factor   | 0.63 | 0.76 | 0.82 |

|                                     |     |
|-------------------------------------|-----|
| Load type                           | : - |
| Load torque                         | : - |
| Load inertia (J=GD <sup>2</sup> /4) | : - |

|                      |                  |               |
|----------------------|------------------|---------------|
|                      | Drive end        | Non drive end |
| Bearing type         | 6206-ZZ          | 6205-ZZ       |
| Lubrication interval | -                | -             |
| Lubricant amount     | -                | -             |
| Lubricant type       | MOBIL POLYREX EM |               |

|                  |   |
|------------------|---|
| Foundation loads |   |
| Max. traction    | : |
| Max. compression | : |

### Notes

See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

| Rev.         | Changes Summary |  | Rev.       | Checked | Date |
|--------------|-----------------|--|------------|---------|------|
|              |                 |  |            |         |      |
| Performed by | farazq          |  | 1851524121 |         |      |
| Checked by   | AUTOMATICO      |  | Page       | Rev.    |      |
| Date         | 22/05/2026      |  | 1 / 2      | 0       |      |

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - ODP - Nema Premium Efficiency      Product code : 12792536

| Thermal protection ID | Application | Type | Quantity | Sensing Temperature |
|-----------------------|-------------|------|----------|---------------------|
|-----------------------|-------------|------|----------|---------------------|

Notes

|           |               |                 |           |                 |
|-----------|---------------|-----------------|-----------|-----------------|
| Standards | Specification | : MG1 - Part 10 | Vibration | : MG1 - Part 7  |
|           | Test          | : MG1 - Part 12 | Tolerance | : MG1 - Part 12 |
|           | Noise         | : MG1 - Part 9  |           |                 |

|                                                                                                                                                                                                                                                               |                                                                                                                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| This revision replaces and cancel the previous one, which must be eliminated.<br>(1) Looking the motor from the shaft end.<br>(2) Measured at 1m and with tolerance of +3dB(A).<br>(3) Approximate weight, subject to be changed after manufacturing process. | These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12. |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|

|              |                 |  |            |         |      |
|--------------|-----------------|--|------------|---------|------|
| Rev.         | Changes Summary |  | Rev.       | Checked | Date |
| Performed by | farazq          |  | 1851524121 |         |      |
| Checked by   | AUTOMATICO      |  | Page       | Rev.    |      |
| Date         | 22/05/2026      |  | 2 / 2      | 0       |      |

