

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 16390827

Frame	: 447/9T	Locked rotor time	: 43s (cold) 24s (hot)
Output	: 200 HP (150 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 190 A	Protection degree	: IP55
L. R. Amperes	: 1251 A	Cooling method	: IC411 - TEFC
LRC	: 6.6x(Code G)	Mounting	: F-1
No load current	: 72.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1187 rpm	Noise level ²	: 70.0 dB(A)
Slip	: 1.08 %	Starting method	: Direct On Line
Rated torque	: 122 kgfm	Approx. weight ³	: 1019 kg
Locked rotor torque	: 229 %		
Breakdown torque	: 240 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 6.09 kgm ²		
Design	: B		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	95.0	95.4	95.8	Max. traction	: 1933 kgf
Power Factor	0.68	0.79	0.83	Max. compression	: 3201 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
4.7	4.0	3.7	2.3	1.7	1.1	0.8

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	NU-322 C3	6319 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	7000 h	13000 h
Lubricant amount	:	60 g	45 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page Revision 1 / 2		
Checked by				
Date	28/08/2026			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 16390827



Performance : 575 V 60 Hz 6P

Rated current : 190 A
LRC : 6.6
Rated torque : 122 kgfm
Locked rotor torque : 229 %
Breakdown torque : 240 %
Rated speed : 1187 rpm

Moment of inertia (J) : 6.09 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 2Revision		
Checked by				
Date	28/08/2026			

