DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W40 High Efficiency Three-Phase Product code : 16504986

Frame	: 444/5T	Locked rotor time	: 36s (cold) 20s (hot)
Output	: 200 HP (150 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 184 A	Protection degree	: IP23
L. R. Amperes	: 1141 A	Cooling method	: IC01 - ODP
LRC	: 6.2x(Code G)	Mounting	: F-1
No load current	: 57.1 A	Rotation[1]	: Both (CW and CCW)
Rated speed	: 1780 rpm	Vibration	: A
Slip	: 1.11 %	Starting method	: Direct On Line
Rated torque	: 81 kgfm	Approx. weight[3]	: 619 kg
Locked rotor torque	: 180 %		: 203A (ISO 12944 - C3)
Breakdown torque	: 210 %		: RAL 3002
Insulation class	: F	Design	: B
Service factor	: 1.15		
Moment of inertia (J)	: 1.78 kgm²		

Output	25%	50%	75%	100%
Efficiency (%)	0.000	94.5	95.0	95.0
Power Factor	0.00	0.77	0.83	0.86

Foundation loads

Max. traction	: 1198 kgf
Max. compression	: 1797 kgf

		Drive end	Non drive end
Bearing type	:	6319 C3	6212 Z C3
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	45 g	13 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	08/10/2026		1 / 2	


This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W40 High Efficiency Three-Phase Product code : 16504986





Performance	: 575 V 60 Hz 4P		
Rated current	: 184 A	Moment of inertia (J)	: 1.78 kgm²
LRC	: 6.2	Duty cycle	: Cont.(S1)
Rated torque	: 81 kgfm	Insulation class	: F
Locked rotor torque	: 180 %	Service factor	: 1.15
Breakdown torque	: 210 %	Temperature rise	: 80 K
Rated speed	: 1780 rpm	Design	: B


Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	08/10/2026		2 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice








Color RAL 3002
Painting plan 203A
Mounting NEMA F-1
Mounting B3R(D)

DE Shaft End



DUNC 3/4"-10 WEG WPR-7339

200 HP 04 Poles 60 Hz | A

Scale 1 : 14

ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
			HYBRISUSER				00

EXECUTED	HYBRISUSER
CHECKED	
RELEASED	
REL. DATE	

THREE PH. MOTOR W40 HIGH EFF.
FRAME 444/5T IP23 ODP

PREVIEW
WDD 00
SHEET 1 / 1

Dimensions in inches

A3

WEG's property. Forbidden reproduction without previous authorization.