

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11568627

Frame	: 444/5T	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 676 kg
Protection degree	: IP55	Moment of inertia (J)	: 3.10 kgm ²
Design	: B		

Output [HP]	75	60	60	60	75	75	75
Poles	8	8	8	8	8	8	8
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	187/93.4	95.5	95.8	94.9	114	109	106
L. R. Amperes [A]	1196/598	525	565	607	536	567	604
LRC [A]	6.4x(Code H)	5.5x(Code G)	5.9x(Code H)	6.4x(Code J)	4.7x(Code E)	5.2x(Code F)	5.7x(Code G)
No load current [A]	80.0/40.0	39.3	43.6	47.0	39.3	43.6	47.0
Rated speed [RPM]	890	740	740	740	735	735	740
Slip [%]	1.11	1.33	1.33	1.33	2.00	2.00	1.33
Rated torque [kgfm]	61.2	58.8	58.8	58.8	74.1	74.1	73.6
Locked rotor torque [%]	170	170	200	220	140	160	180
Breakdown torque [%]	200	210	229	250	170	190	210
Service factor	1.25	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	32s (cold) 18s (hot)	72s (cold) 40s (hot)	64s (cold) 36s (hot)	61s (cold) 34s (hot)	46s (cold) 26s (hot)	46s (cold) 26s (hot)	48s (cold) 27s (hot)
Noise level ²	63.0 dB(A)	59.0 dB(A)	59.0 dB(A)	59.0 dB(A)	59.0 dB(A)	59.0 dB(A)	59.0 dB(A)
Efficiency (%)	25%						
	50%	93.0	92.6	91.3	91.2	91.5	92.0
	75%	93.6	93.0	92.6	92.5	91.7	92.4
	100%	93.6	93.0	92.9	92.9	91.7	92.4
Power Factor	25%						
	50%	0.64	0.56	0.52	0.49	0.70	0.63
	75%	0.74	0.69	0.65	0.62	0.77	0.73
	100%	0.79	0.77	0.73	0.71	0.80	0.78

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	6.6	6.6	6.6	6.6	6.6	6.6
	P2 (0,5;1,0)	5.2	5.2	5.2	5.2	5.2	5.2
	P3 (0,25;1,0)	4.7	4.7	4.7	4.7	4.7	4.7
	P4 (0,9;0,5)	3.3	3.3	3.3	3.3	3.3	3.3
	P5 (0,5;0,5)	2.2	2.2	2.2	2.2	2.2	2.2
	P6 (0,5;0,25)	1.5	1.5	1.5	1.5	1.5	1.5
	P7 (0,25;0,25)	1.0	1.0	1.0	1.0	1.0	1.0

Bearing type	Drive end	Non drive end	Foundation loads
	: 6319 C3	6316 C3	
	Sealing	WSeal	
	Lubrication interval	17000 h	
	Lubricant amount	45 g	
Lubricant type	Mobil Polyrex EM		Max. traction : 1013 kgf
			Max. compression : 1689 kgf

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	30/10/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes
USABLE @208V 206A SF 1.10 SFA 226A

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 9		Revision
Checked by					
Date	30/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11568627



Performance : 230/460 V 60 Hz 8P

Rated current : 187/93.4 A
LRC : 6.4
Rated torque : 61.2 kgfm
Locked rotor torque : 170 %
Breakdown torque : 200 %
Rated speed : 890 rpm

Moment of inertia (J) : 3.10 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by			Page		Revision
Date	30/10/2024		3 / 9		

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11568627



Performance : 380 V 50 Hz 8P IE3

Rated current : 95.5 A
LRC : 5.5
Rated torque : 58.8 kgfm
Locked rotor torque : 170 %
Breakdown torque : 210 %
Rated speed : 740 rpm

Moment of inertia (J) : 3.10 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11568627



Performance : 400 V 50 Hz 8P IE3

Rated current : 95.8 A
LRC : 5.9
Rated torque : 58.8 kgfm
Locked rotor torque : 200 %
Breakdown torque : 229 %
Rated speed : 740 rpm

Moment of inertia (J) : 3.10 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 9 Revision		
Checked by				
Date	30/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11568627

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 8P IE3

Rated current	: 94.9 A	Moment of inertia (J)	: 3.10 kgm ²
LRC	: 6.4	Duty cycle	: Cont.(S1)
Rated torque	: 58.8 kgfm	Insulation class	: F
Locked rotor torque	: 220 %	Service factor	: 1.00
Breakdown torque	: 250 %	Temperature rise	: 80 K
Rated speed	: 740 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 6 / 9 Revision			
Checked by					
Date	30/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11568627



Performance : 380 V 50 Hz 8P IE2

Rated current : 114 A
LRC : 4.7
Rated torque : 74.1 kgfm
Locked rotor torque : 140 %
Breakdown torque : 170 %
Rated speed : 735 rpm

Moment of inertia (J) : 3.10 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 7 / 9Revision		
Checked by				
Date	30/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11568627



Performance : 400 V 50 Hz 8P IE2

Rated current : 109 A
LRC : 5.2
Rated torque : 74.1 kgfm
Locked rotor torque : 160 %
Breakdown torque : 190 %
Rated speed : 735 rpm

Moment of inertia (J) : 3.10 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				8 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11568627






Performance : 415 V 50 Hz 8P IE2

Rated current : 106 A
LRC : 5.7
Rated torque : 73.6 kgfm
Locked rotor torque : 180 %
Breakdown torque : 210 %
Rated speed : 740 rpm

Moment of inertia (J) : 3.10 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 9 / 9	Revision
Checked by					
Date	30/10/2024				



Without vertical jackscrews
Color RAL 5009
Painting plan 203A
Mounting B3R(D)

75 HP 08 Poles 60 Hz										A
							HYBRISUSER			
ECM		LOC		SUMMARY OF MODIFICATIONS			EXECUTED		CHECKED	
							RELEASED		DATE	
							VER		00	
EXECUTED		HYBRISUSER		 THREE PH. MOTOR W22 NEMA PREM. EFF. FRAME 444/5T IP55 TEFC			PREVIEW WDD 00			
CHECKED										
RELEASED										
REL. DATE										