DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer	:

Product line	: W22 P-base - Nema Premium Efficiency
Product code	: 16614519

Frame	: 364/5HP	Locked rotor time	: 21 s (hot) 38 s (cold)
Output	: 40 HP (30 kW)	Temperature rise[4]	: 80 K
Poles	: 6	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20 °C to +40 °C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l
Rated current	: 37.2 A	Protection degree	: IP55
L. R. Amperes	: 238 A	Cooling method	: IC411 - TEFC
LRC	: 6.4 Code G	Mounting	: V1
No load current	: 13.2 A	Rotation[1]	: Both
Rated speed	: 1183 rpm	Noise level[2]	: 66 dB(A)
Slip	: 1.42 %	Starting method	: Direct On Line
Rated torque	: 24.5 kgfm	Approx. weight[3]	: 378 kg
Locked rotor torque	: 200 %	Design	: B
Pull up torque	: 160 %		
Breakdown torque	: 240 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.9189 kgm²		

Output	Start	50%	75%	100%
Efficiency (%)	-	93.6	93.6	94.1
Power Factor	0.39	0.73	0.82	0.86

Load type	: -
Load torque	: -
Load inertia (J=GD²/4)	: -

	Drive end	Non drive end
Bearing type	6316-C3	6314-C3
Lubrication interval	8000 h	8000 h
Lubricant amount	34 g	27 g
Lubricant type	MOBIL POLYREX EM	

Notes:

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
6.13	5.04	4.42	2.81	1.86	1.15	0.76

Standards

Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated..
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +0dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Performed	Checked	Date
				2026/11/23


Performed by				
Checked by			Page	Revision
Date	2026/11/23		1/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:
Product line	: W22 P-base - Nema Premium Efficiency
Product code	: 16614519




Performance	: 40 HP (30 kW) 575V 60Hz 6P 364/5HP


Rated current	: 37.2 A	Moment of inertia (J)	: 0.9189 kgm²
LRC	: 6.4 Code G	Duty cycle	: Cont.(S1)
Rated torque	: 24.5 kgfm	Insulation class	: F
Locked rotor torque	: 200 %	Service factor	: 1.25
Breakdown torque	: 240 %	Temperature rise	: 80 K
Rated speed	: 1183 rpm	Design	: B


Rev.	Changes Summary	Performed	Checked	Date
				2026/11/23


Performed by				
Checked by			Page	Revision
Date	2026/11/23		2/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.










Internal AEGIS ground ring on the DE
With drip cover
Color RAL 5009
Painting plan 203A
Mounting NEMA W-6
Mounting V1

DE Shaft End



DUNC 5/8"-11 WEG WPR-7339

40 HP 06 Poles 60 Hz | A

Scale 1 : 11

ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
			HYBRISUSER				00

EXECUTED	HYBRISUSER
CHECKED	
RELEASED	
REL. DATE	

THREE PH. MOTOR W22 P. BASE NEMA PREM. EFF.
FRAME 364/5HP IP55 TEFC

PREVIEW

WDD 00

SHEET 1 / 1

Dimensions in inches

A3

WEG's property. Forbidden reproduction without previous authorization.