

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :				
Product line : Three-Phase		Product code : 13989585		
Frame : 56C	Insulation class : F	Cooling method : IC411 - TEFC	Mounting : F-1	
Duty cycle : Cont.(S1)	Ambient temperature : -20°C to +40°C	Rotation ¹ : Both (CW and CCW)	Starting method : Direct On Line	
Altitude : 1000 m.a.s.l.	Protection degree : IP55	Approx. weight ³ : 12.8 kg	Moment of inertia (J) : 0.0036 kgm ²	
Output [HP]	0.75			
Poles	4			
Frequency [Hz]	60			
Rated voltage [V]	575			
Rated current [A]	0.952			
L. R. Amperes [A]	7.33			
LRC [A]	7.7x(Code L)			
No load current [A]	0.658			
Rated speed [RPM]	1760			
Slip [%]	2.22			
Rated torque [kgfm]	0.309			
Locked rotor torque [%]	240			
Breakdown torque [%]	360			
Service factor	1.15			
Temperature rise	80 K			
Locked rotor time	28s (cold) 16s (hot)			
Noise level ²	52.0 dB(A)			
Efficiency (%)	25%			
	50%	75.5		
	75%	80.0		
	100%	81.5		
Power Factor	25%			
	50%	0.49		
	75%	0.62		
	100%	0.71		
Bearing type : 6203 ZZ	Drive end	Non drive end	Foundation loads	
Sealing : V'Ring			Max. traction : 29 kgf	
Lubrication interval : -			Max. compression : 42 kgf	
Lubricant amount : -				
Lubricant type : Mobil Polyrex EM				
Notes				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				
These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.				
Rev.	Changes Summary		Performed	Checked
Performed by				
Checked by				
Date	13/05/2022		Page	Revision
			1 / 2	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Three-Phase

Product code : 13989585



Performance : 575 V 60 Hz 4P

Rated current : 0.952 A
 LRC : 7.7
 Rated torque : 0.309 kgfm
 Locked rotor torque : 240 %
 Breakdown torque : 360 %
 Rated speed : 1760 rpm

Moment of inertia (J) : 0.0036 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor : 1.15
 Temperature rise : 80 K

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 2Revision		
Checked by				
Date	13/05/2022			

