

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer	:			
Product line	: Single-Phase	Product code : 13490020		
Frame	: 56HC	Cooling method : IC411 - TEFC		
Insulation class	: F	Mounting : F-1		
Duty cycle	: Cont.(S1)	Rotation ¹ : Both (CW and CCW)		
Ambient temperature	: -20°C to +40°C	Starting method : Direct On Line		
Altitude	: 1000 m.a.s.l.	Approx. weight ³ : 20.8 kg		
Protection degree	: IP55	Moment of inertia (J) : 0.0082 kgm ²		
Design	: L			
Output [HP]		1		
Poles		6		
Frequency [Hz]		60		
Rated voltage [V]		115/208-230		
Rated current [A]		11.0/6.08-5.50		
L. R. Amperes [A]		67.1/37.1-33.5		
LRC [A]		6.1x(Code J)		
No load current [A]		5.60/2.41-2.80		
Rated speed [RPM]		1165		
Slip [%]		2.92		
Rated torque [kgfm]		0.623		
Locked rotor torque [%]		180		
Breakdown torque [%]		200		
Service factor				
Temperature rise		80 K		
Locked rotor time		23s (cold) 13s (hot)		
Noise level ²		54.0 dB(A)		
Efficiency (%)	25%			
	50%	64.0		
	75%	71.0		
	100%	73.0		
Power Factor	25%			
	50%	0.68		
	75%	0.77		
	100%	0.81		
Bearing type	: Drive end : 6204 ZZ Non drive end : 6202 ZZ	Foundation loads		
Sealing	: V'Ring Without Bearing Seal	Max. traction : 29 kgf		
Lubrication interval	: - -	Max. compression : 50 kgf		
Lubricant amount	: - -			
Lubricant type	: Mobil Polyrex EM			
Notes				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	13/05/2022		1 / 2	

LOAD PERFORMANCE CURVE

Single Phase Induction Motor - Squirrel Cage




Customer :

Product line : Single-Phase

Product code : 13490020

LOAD PERFORMANCE CURVE



Performance : 115/208-230 V 60 Hz 6P

Rated current : 11.0/6.08-5.50 A
 LRC : 6.1
 Rated torque : 0.623 kgfm
 Locked rotor torque : 180 %
 Breakdown torque : 200 %
 Rated speed : 1165 rpm

Moment of inertia (J) : 0.0082 kgm²
 Duty cycle : Cont.(S1)
 Insulation class : F
 Service factor :
 Temperature rise : 80 K
 Design : L

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	13/05/2022			

