

DATA SHEET




Three Phase Induction Motor - Squirrel Cage

Customer :							
Product line		: W22 Brake Motor NEMA Premium Efficiency Three-Phase		Product code :		14532255	
Frame	:	254/6TC		Locked rotor time	:	37s (cold) 21s (hot)	
Output	:	15 HP (11 kW)		Temperature rise	:	80 K	
Frequency	:	60 Hz		Duty cycle	:	Cont.(S1)	
Rated voltage	:	575 V		Ambient temperature	:	-20°C to +40°C	
Poles	:	4		Altitude	:	1000 m.a.s.l.	
Rated current	:	14.4 A		Protection degree	:	IP55	
	:	6.4x(Code G)		Cooling method	:	IC411 - TEFC	
Rated speed	:	1770 rpm		Mounting	:	F-1	
Rated torque	:	6.15 kgfm		Rotation ¹	:	Both (CW and CCW)	
Insulation class	:	F		Noise level ²	:	64.0 dB(A)	
Service factor	:	1.25		Starting method	:	Direct On Line	
Moment of inertia (J)	:	0.1104 kgm ²		Approx. weight ³	:	152 kg	
Design	:	B					
Output	25%	50%	75%	100%	Foundation loads		
Efficiency (%)	0.000	91.0	91.7	92.4	Max. traction	: 166 kgf	
Power Factor	0.00	0.68	0.78	0.83	Max. compression	: 317 kgf	
Losses at normative operating points (speed;torque), in percentage of rated output power							
P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)	
8.1	7.0	6.5	3.9	2.8	1.8	1.3	
		<u>Drive end</u>		<u>Non drive end</u>			
Bearing type	:	6309 C3		6209 C3			
Sealing	:	V'Ring		Lip Seal			
Lubrication interval	:	20000 h		20000 h			
Lubricant amount	:	13 g		9 g			
Lubricant type	:	Mobil Polyrex EM					
Notes							
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.				These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.	Changes Summary			Performed	Checked	Date	
Performed by							
Checked by					Page	Revision	
Date	26/04/2026				1 / 3		

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Brake information

Voltage: 525-575 V
Brake Torque: 15.3 kgfm

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	26/04/2026		2 / 3	


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :


Product line : W22 Brake Motor NEMA Premium Efficiency Three-Phase Product code : 14532255



Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 3 / 3	Revision
Checked by				
Date				



Without vertical jackscrews
Break size 18 (150 Nm)
Brake voltage 525-575 V
Color RAL 5009
Painting plan 203A
Mounting NEMA F-1
Mounting B34D



15 HP 04 Poles 60 Hz										A
Scale 1 : 8										
HYBRISUSER										00
ECM	LOC	SUMMARY OF MODIFICATIONS				EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	HYBRISUSER	THREE PH. MOTOR W22 BRAKE MOTOR NEMA PREM. EFF.				EXECUTED	CHECKED	RELEASED	DATE	VER
CHECKED		FRAME 254/6TC IP55 TEFC				EXECUTED	CHECKED	RELEASED	DATE	VER
RELEASED						EXECUTED	CHECKED	RELEASED	DATE	VER
REL. DATE						EXECUTED	CHECKED	RELEASED	DATE	VER
						PREVIEW		WDD 00		
						SHEET 1 / 1				