

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer	:			
Product line	: Standard Efficiency Three-Phase	Product code : 13326285		
Frame	: 56HC	Cooling method : IC411 - TEFC		
Insulation class	: F	Mounting : F-1		
Duty cycle	: Cont.(S1)	Rotation ¹ : Both (CW and CCW)		
Ambient temperature	: -20°C to +40°C	Starting method : Direct On Line		
Altitude	: 1000 m.a.s.l.	Approx. weight ³ : 17.0 kg		
Protection degree	: IP55	Moment of inertia (J) : 0.0052 kgm ²		
Design	: A			
Output [HP]		2		
Poles		4		
Frequency [Hz]		60		
Rated voltage [V]		575		
Rated current [A]		2.28		
L. R. Amperes [A]		16.6		
LRC [A]		7.3x(Code K)		
No load current [A]		1.33		
Rated speed [RPM]		1745		
Slip [%]		3.06		
Rated torque [kgfm]		0.832		
Locked rotor torque [%]		240		
Breakdown torque [%]		270		
Service factor		1.15		
Temperature rise		80 K		
Locked rotor time		14s (cold) 8s (hot)		
Noise level ²		52.0 dB(A)		
Efficiency (%)	25%			
	50%	80.0		
	75%	81.5		
	100%	82.5		
Power Factor	25%			
	50%	0.58		
	75%	0.72		
	100%	0.80		
Bearing type	: Drive end : 6204 ZZ Non drive end : 6202 ZZ	Foundation loads		
Sealing	: V'Ring V'Ring	Max. traction : 64 kgf		
Lubrication interval	: - -	Max. compression : 81 kgf		
Lubricant amount	: - -			
Lubricant type	: Mobil Polyrex EM			
Notes				
<p>This revision replaces and cancel the previous one, which must be eliminated.</p> <p>(1) Looking the motor from the shaft end.</p> <p>(2) Measured at 1m and with tolerance of +3dB(A).</p> <p>(3) Approximate weight subject to changes after manufacturing process.</p> <p>(4) At 100% of full load.</p>		<p>These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.</p>		
Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	13/05/2022		1 / 2	

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : Standard Efficiency Three-Phase Product code : 13326285

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 4P

Rated current	: 2.28 A	Moment of inertia (J)	: 0.0052 kgm ²
LRC	: 7.3	Duty cycle	: Cont.(S1)
Rated torque	: 0.832 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	: 1.15
Breakdown torque	: 270 %	Temperature rise	: 80 K
Rated speed	: 1745 rpm	Design	: A

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page 2 / 2	Revision
Checked by				
Date	13/05/2022			

