

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 12447064

Frame	: 324/6T	Locked rotor time	: 36s (cold) 20s (hot)
Output	: 20 HP (15 kW)	Temperature rise	: 80 K
Poles	: 8	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 23.9 A	Protection degree	: IP55
L. R. Amperes	: 119 A	Cooling method	: IC411 - TEFC
LRC	: 5.0x(Code G)	Mounting	: F-1
No load current	: 13.6 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 881 rpm	Noise level ²	: 56.0 dB(A)
Slip	: 2.11 %	Vibration	: A
Rated torque	: 16 kgfm	Starting method	: Direct On Line
Locked rotor torque	: 190 %	Approx. weight ³	: 205 kg
Breakdown torque	: 220 %	Painting plan	: 203A (ISO 12944 - C3)
Insulation class	: F	Color	: RAL 5009
Service factor	: 1.25	Design	: B
Moment of inertia (J)	: 0.3946 kgm ²		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	89.5	90.2	90.2	Max. traction	: 346 kgf
Power Factor	0.50	0.63	0.70	Max. compression	: 566 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
10.5	8.9	8.6	5.8	4.2	3.2	2.4

	Drive end	Non drive end
Bearing type	: 6312 C3	6212 C3
Sealing	: V'Ring	V'Ring
Lubrication interval	: 20000 h	20000 h
Lubricant amount	: 21 g	13 g
Lubricant type	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/09/2026			

Page 1 / 2
Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 12447064







Performance : 575 V 60 Hz 8P

Rated current : 23.9 A
LRC : 5.0
Rated torque : 16 kgfm
Locked rotor torque : 190 %
Breakdown torque : 220 %
Rated speed : 881 rpm

Moment of inertia (J) : 0.3946 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date					



Without vertical jackscrews

Color RAL 5009

Painting plan 203A

Mounting B3R(D)

20 HP 08 Poles 60 Hz

Dimensions in inches

A3

Scale 1 : 10

	HYBRISUSER
--	------------

10	
----	--

ECM

LOC

SUMMARY OF MODIFICATIONS

EXECUTED

CHECKED


RELEASED

DATE _____

ER

EXECUTED

HYBRISUSER		
------------	--	--



THREE PH. MOTOR W22 NEMA PREM. EFF.

FRAME 324/6T IP55 TEFC

PREVIEW

WDD

00



	SHEET
--	-------

1	/	1
---	---	---

WEG's property. Forbidden reproduction without previous authorization.