

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11355046

Frame	: 404/5T	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 523 kg
Protection degree	: IP55	Moment of inertia (J)	: 1.55 kgm ²
Design	: B		

Output [HP]	60	50	50	50	60	60	60
Poles	6	6	6	6	6	6	6
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	230/460	380	400	415	380	400	415
Rated current [A]	139/69.5	69.3	66.5	64.8	85.1	80.3	78.3
L. R. Amperes [A]	987/493	457	485	505	477	498	525
LRC [A]	7.1x(Code H)	6.6x(Code G)	7.3x(Code H)	7.8x(Code J)	5.6x(Code F)	6.2x(Code G)	6.7x(Code G)
No load current [A]	50.0/25.0	24.7	26.4	27.7	24.7	26.4	27.7
Rated speed [RPM]	1185	985	985	985	980	980	985
Slip [%]	1.25	1.50	1.50	1.50	2.00	2.00	1.50
Rated torque [kgfm]	36.7	36.8	36.8	36.8	44.4	44.4	44.2
Locked rotor torque [%]	200	180	220	229	150	180	190
Breakdown torque [%]	229	220	240	260	180	200	220
Service factor	1.25	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	36s (cold) 20s (hot)	28s (cold) 16s (hot)	28s (cold) 16s (hot)	28s (cold) 16s (hot)	28s (cold) 16s (hot)	28s (cold) 16s (hot)	28s (cold) 16s (hot)
Noise level ²	68.0 dB(A)	64.0 dB(A)	64.0 dB(A)	64.0 dB(A)	64.0 dB(A)	64.0 dB(A)	64.0 dB(A)
Efficiency (%)	25%						
	50%	94.1	93.3	93.3	93.3	93.6	93.6
	75%	94.5	93.4	93.7	93.7	93.0	93.6
	100%	94.5	93.3	93.4	93.4	92.4	93.0
Power Factor	25%						
	50%	0.74	0.73	0.70	0.67	0.79	0.77
	75%	0.82	0.83	0.82	0.79	0.85	0.84
	100%	0.86	0.87	0.86	0.85	0.87	0.86

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	5.6	5.6	5.6	5.6	5.6	5.6
	P2 (0,5;1,0)	4.6	4.6	4.6	4.6	4.6	4.6
	P3 (0,25;1,0)	4.3	4.3	4.3	4.3	4.3	4.3
	P4 (0,9;0,5)	2.6	2.6	2.6	2.6	2.6	2.6
	P5 (0,5;0,5)	1.8	1.8	1.8	1.8	1.8	1.8
	P6 (0,5;0,25)	1.1	1.1	1.1	1.1	1.1	1.1
	P7 (0,25;0,25)	0.7	0.7	0.7	0.7	0.7	0.7

Bearing type	: 6316 C3	Non drive end	6314 C3	Foundation loads	
Sealing	: WSeal	WSeal		Max. traction	: 696 kgf
Lubrication interval	: 16000 h	17000 h		Max. compression	: 1219 kgf
Lubricant amount	: 34 g	27 g			
Lubricant type	: Mobil Polyrex EM				

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	21/10/2024		Page 1 / 9	Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes
USABLE @208V 154A SF 1.10 SFA 169A

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 9		Revision
Checked by					
Date	21/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11355046



Performance : 230/460 V 60 Hz 6P

Rated current : 139/69.5 A
LRC : 7.1
Rated torque : 36.7 kgfm
Locked rotor torque : 200 %
Breakdown torque : 229 %
Rated speed : 1185 rpm

Moment of inertia (J) : 1.55 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 3 / 9	Revision
Checked by					
Date	21/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11355046



Performance : 380 V 50 Hz 6P IE3

Rated current	: 69.3 A	Moment of inertia (J)	: 1.55 kgm ²
LRC	: 6.6	Duty cycle	: Cont.(S1)
Rated torque	: 36.8 kgfm	Insulation class	: F
Locked rotor torque	: 180 %	Service factor	: 1.00
Breakdown torque	: 220 %	Temperature rise	: 80 K
Rated speed	: 985 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 9	
Date	21/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11355046



Performance : 400 V 50 Hz 6P IE3

Rated current : 66.5 A
LRC : 7.3
Rated torque : 36.8 kgfm
Locked rotor torque : 220 %
Breakdown torque : 240 %
Rated speed : 985 rpm

Moment of inertia (J) : 1.55 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 9Revision		
Checked by				
Date	21/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11355046



Performance : 415 V 50 Hz 6P IE3

Rated current : 64.8 A
LRC : 7.8
Rated torque : 36.8 kgfm
Locked rotor torque : 229 %
Breakdown torque : 260 %
Rated speed : 985 rpm

Moment of inertia (J) : 1.55 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				6 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11355046



Performance : 380 V 50 Hz 6P IE1

Rated current : 85.1 A
LRC : 5.6
Rated torque : 44.4 kgfm
Locked rotor torque : 150 %
Breakdown torque : 180 %
Rated speed : 980 rpm

Moment of inertia (J) : 1.55 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 7 / 9Revision		
Checked by				
Date	21/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11355046



Performance : 400 V 50 Hz 6P IE2

Rated current : 80.3 A
LRC : 6.2
Rated torque : 44.4 kgfm
Locked rotor torque : 180 %
Breakdown torque : 200 %
Rated speed : 980 rpm

Moment of inertia (J) : 1.55 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				8 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency
Three-Phase

Product code : 11355046





Performance : 415 V 50 Hz 6P IE2

Rated current : 78.3 A
LRC : 6.7
Rated torque : 44.2 kgfm
Locked rotor torque : 190 %
Breakdown torque : 220 %
Rated speed : 985 rpm

Moment of inertia (J) : 1.55 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 9 / 9Revision		
Checked by				
Date	21/10/2024			



60 HP 06 Poles 60 Hz

Dimensions in inches

A3