

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase Product code : 11359238

|                       |                         |                             |                        |
|-----------------------|-------------------------|-----------------------------|------------------------|
| Frame                 | : 444/5T                | Locked rotor time           | : 36s (cold) 20s (hot) |
| Output                | : 100 HP (75 kW)        | Temperature rise            | : 80 K                 |
| Poles                 | : 6                     | Duty cycle                  | : Cont.(S1)            |
| Frequency             | : 60 Hz                 | Ambient temperature         | : -20°C to +40°C       |
| Rated voltage         | : 575 V                 | Altitude                    | : 1000 m.a.s.l.        |
| Rated current         | : 96.7 A                | Protection degree           | : IP55                 |
| L. R. Amperes         | : 599 A                 | Cooling method              | : IC411 - TEFC         |
| LRC                   | : 6.2x(Code G)          | Mounting                    | : F-1                  |
| No load current       | : 36.0 A                | Rotation <sup>1</sup>       | : Both (CW and CCW)    |
| Rated speed           | : 1189 rpm              | Noise level <sup>2</sup>    | : 69.0 dB(A)           |
| Slip                  | : 0.92 %                | Starting method             | : Direct On Line       |
| Rated torque          | : 61.0 kgfm             | Approx. weight <sup>3</sup> | : 699 kg               |
| Locked rotor torque   | : 220 %                 |                             |                        |
| Breakdown torque      | : 250 %                 |                             |                        |
| Insulation class      | : F                     |                             |                        |
| Service factor        | : 1.25                  |                             |                        |
| Moment of inertia (J) | : 3.68 kgm <sup>2</sup> |                             |                        |
| Design                | : B                     |                             |                        |

|                |      |      |      |                  |            |
|----------------|------|------|------|------------------|------------|
| Output         | 50%  | 75%  | 100% | Foundation loads |            |
| Efficiency (%) | 94.5 | 95.0 | 95.0 | Max. traction    | : 985 kgf  |
| Power Factor   | 0.68 | 0.78 | 0.82 | Max. compression | : 1684 kgf |

Losses at normative operating points (speed;torque), in percentage of rated output power

| P1 (0,9;1,0) | P2 (0,5;1,0) | P3 (0,25;1,0) | P4 (0,9;0,5) | P5 (0,5;0,5) | P6 (0,5;0,25) | P7 (0,25;0,25) |
|--------------|--------------|---------------|--------------|--------------|---------------|----------------|
| 5.2          | 4.2          | 3.8           | 2.8          | 1.8          | 1.3           | 0.9            |

|                      | Drive end        | Non drive end |
|----------------------|------------------|---------------|
| Bearing type         | : 6319 C3        | 6316 C3       |
| Sealing              | : WSeal          | WSeal         |
| Lubrication interval | : 13000 h        | 16000 h       |
| Lubricant amount     | : 45 g           | 34 g          |
| Lubricant type       | Mobil Polyrex EM |               |

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev.         | Changes Summary | Performed | Checked       | Date     |
|--------------|-----------------|-----------|---------------|----------|
|              |                 |           |               |          |
| Performed by |                 |           |               |          |
| Checked by   |                 |           |               |          |
| Date         | 21/10/2024      |           | Page<br>1 / 2 | Revision |

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 NEMA Premium Efficiency  
Three-Phase

Product code : 11359238



Performance : 575 V 60 Hz 6P

Rated current : 96.7 A  
LRC : 6.2  
Rated torque : 61.0 kgfm  
Locked rotor torque : 220 %  
Breakdown torque : 250 %  
Rated speed : 1189 rpm

Moment of inertia (J) : 3.68 kgm<sup>2</sup>  
Duty cycle : Cont.(S1)  
Insulation class : F  
Service factor : 1.25  
Temperature rise : 80 K  
Design : B

| Rev.         | Changes Summary |  | Performed | Checked | Date     |
|--------------|-----------------|--|-----------|---------|----------|
|              |                 |  |           |         |          |
| Performed by |                 |  |           | Page    | Revision |
| Checked by   |                 |  |           | 2 / 2   |          |
| Date         |                 |  |           |         |          |

