

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11943229

Frame : 404/5T	Cooling method : IC411 - TEFC
Insulation class : F	Mounting : F-1
Duty cycle : Cont.(S1)	Rotation ¹ : Both (CW and CCW)
Ambient temperature : -20°C to +40°C	Starting method : Direct On Line
Altitude : 1000 m.a.s.l.	Approx. weight ³ : 0.0 kg
Protection degree : IP55	Moment of inertia (J) : 1.46 kgm ²
Design : B	

Output [HP]	50	40	40	40	50	50	50
Poles	8	8	8	8	8	8	8
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	460	380	400	415	380	400	415
Rated current [A]	60.2	59.4	57.6	56.8	73.3	69.9	68.2
L. R. Amperes [A]	433	404	420	443	403	419	443
LRC [A]	7.2x(Code H)	6.8x(Code H)	7.3x(Code J)	7.8x(Code J)	5.5x(Code F)	6.0x(Code G)	6.5x(Code H)
No load current [A]	24.5	23.5	25.0	26.0	23.0	25.0	26.0
Rated speed [RPM]	880	730	733	735	720	725	725
Slip [%]	2.22	2.67	2.27	2.00	4.00	3.33	3.33
Rated torque [kgfm]	41.2	39.8	39.6	39.5	50.4	50.1	50.1
Locked rotor torque [%]	170	170	200	229	140	160	180
Breakdown torque [%]	260	240	290	310	200	229	250
Service factor	1.25	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	52s (cold) 29s (hot)	57s (cold) 32s (hot)	54s (cold) 30s (hot)	50s (cold) 28s (hot)	36s (cold) 20s (hot)	37s (cold) 21s (hot)	36s (cold) 20s (hot)
Noise level ²	60.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)
Efficiency (%)	25%						
	50%	93.0	92.9	91.8	91.8	92.4	92.4
	75%	93.0	92.3	92.2	92.2	91.7	91.7
	100%	93.0	91.3	91.7	91.8	90.2	91.0
Power Factor	25%						
	50%	0.68	0.65	0.63	0.60	0.74	0.68
	75%	0.78	0.78	0.76	0.73	0.82	0.78
	100%	0.83	0.84	0.82	0.80	0.85	0.83

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	7.3	7.3	7.3	7.3	7.3	7.3
	P2 (0,5;1,0)	6.3	6.3	6.3	6.3	6.3	6.3
	P3 (0,25;1,0)	6.3	6.3	6.3	6.3	6.3	6.3
	P4 (0,9;0,5)	3.0	3.0	3.0	3.0	3.0	3.0
	P5 (0,5;0,5)	2.2	2.2	2.2	2.2	2.2	2.2
	P6 (0,5;0,25)	1.3	1.3	1.3	1.3	1.3	1.3
	P7 (0,25;0,25)	0.9	0.9	0.9	0.9	0.9	0.9

Bearing type : 6316 C3	Non drive end : 6314 C3	Foundation loads
Sealing : Taconite	Taconite	Max. traction : 1232 kgf
	Labyrinth	Max. compression : 1232 kgf
Lubrication interval : 20000 h	20000 h	
Lubricant amount : 34 g	27 g	
Lubricant type : Mobil Polyrex EM		

Rev.	Changes Summary	Performed	Checked	Date
Performed by				Page 1 / 9
Checked by				
Date				
22/10/2024				Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page		Revision
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943229



Performance : 460 V 60 Hz 8P

Rated current : 60.2 A
LRC : 7.2
Rated torque : 41.2 kgfm
Locked rotor torque : 170 %
Breakdown torque : 260 %
Rated speed : 880 rpm

Moment of inertia (J) : 1.46 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 9Revision		
Checked by				
Date	22/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11943229

LOAD PERFORMANCE CURVE



Performance : 380 V 50 Hz 8P IE3

Rated current	: 59.4 A	Moment of inertia (J)	: 1.46 kgm ²
LRC	: 6.8	Duty cycle	: Cont.(S1)
Rated torque	: 39.8 kgfm	Insulation class	: F
Locked rotor torque	: 170 %	Service factor	: 1.00
Breakdown torque	: 240 %	Temperature rise	: 80 K
Rated speed	: 730 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 4 / 9Revision			
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943229



Performance : 400 V 50 Hz 8P IE3

Rated current : 57.6 A
LRC : 7.3
Rated torque : 39.6 kgfm
Locked rotor torque : 200 %
Breakdown torque : 290 %
Rated speed : 733 rpm

Moment of inertia (J) : 1.46 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 9Revision		
Checked by				
Date	22/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943229



Performance : 415 V 50 Hz 8P IE3

Rated current : 56.8 A
LRC : 7.8
Rated torque : 39.5 kgfm
Locked rotor torque : 229 %
Breakdown torque : 310 %
Rated speed : 735 rpm

Moment of inertia (J) : 1.46 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				6 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943229



Performance : 380 V 50 Hz 8P IE1

Rated current : 73.3 A
LRC : 5.5
Rated torque : 50.4 kgfm
Locked rotor torque : 140 %
Breakdown torque : 200 %
Rated speed : 720 rpm

Moment of inertia (J) : 1.46 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 7 / 9Revision		
Checked by				
Date	22/10/2024			


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11943229



Performance : 400 V 50 Hz 8P IE2

Rated current	: 69.9 A	Moment of inertia (J)	: 1.46 kgm ²
LRC	: 6.0	Duty cycle	: Cont.(S1)
Rated torque	: 50.1 kgfm	Insulation class	: F
Locked rotor torque	: 160 %	Service factor	: 1.00
Breakdown torque	: 229 %	Temperature rise	: 105 K
Rated speed	: 725 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 8 / 9Revision			
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943229



Performance : 415 V 50 Hz 8P IE2

Rated current : 68.2 A
LRC : 6.5
Rated torque : 50.1 kgfm
Locked rotor torque : 180 %
Breakdown torque : 250 %
Rated speed : 725 rpm

Moment of inertia (J) : 1.46 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 9 / 9	Revision
Checked by					
Date	22/10/2024				

