

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11943424

Frame	: 364/5TS	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 0.0 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.5023 kgm ²
Design	: B		

Output [HP]	75	50	50	50	75	75	75
Poles	2	2	2	2	2	2	2
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	460	380	400	415	380	400	415
Rated current [A]	81.9	66.7	64.8	62.4	100	94.8	91.4
L. R. Amperes [A]	541	520	551	568	520	550	567
LRC [A]	6.6x(Code G)	7.8x(Code H)	8.5x(Code J)	9.1x(Code K)	5.2x(Code E)	5.8x(Code F)	6.2x(Code F)
No load current [A]	19.0	18.0	19.0	20.0	18.0	19.0	20.0
Rated speed [RPM]	3550	2960	2965	2970	2930	2940	2950
Slip [%]	1.39	1.33	1.17	1.00	2.33	2.00	1.67
Rated torque [kgfm]	15.3	12.3	12.2	12.2	18.6	18.5	18.5
Locked rotor torque [%]	220	240	260	290	160	175	190
Breakdown torque [%]	270	320	350	380	200	220	240
Service factor	1.25	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	18s (cold) 10s (hot)	12s (cold) 7s (hot)	12s (cold) 7s (hot)	12s (cold) 7s (hot)	12s (cold) 7s (hot)	12s (cold) 7s (hot)	12s (cold) 7s (hot)
Noise level ²	79.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)	74.0 dB(A)
Efficiency (%)	25%						
	50%	92.4	91.2	91.5	91.8	92.4	93.0
	75%	93.6	92.5	93.0	93.1	93.0	93.6
	100%	93.6	93.7	93.7	93.7	92.4	93.0
Power Factor	25%						
	50%	0.83	0.75	0.72	0.70	0.86	0.83
	75%	0.88	0.85	0.83	0.82	0.90	0.88
	100%	0.90	0.90	0.88	0.88	0.90	0.90

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	6.4	6.4	6.4	6.4	6.4	6.4
	P2 (0,5;1,0)	4.9	4.9	4.9	4.9	4.9	4.9
	P3 (0,25;1,0)	4.7	4.7	4.7	4.7	4.7	4.7
	P4 (0,9;0,5)	3.1	3.1	3.1	3.1	3.1	3.1
	P5 (0,5;0,5)	1.8	1.8	1.8	1.8	1.8	1.8
	P6 (0,5;0,25)	1.0	1.0	1.0	1.0	1.0	1.0
	P7 (0,25;0,25)	0.6	0.6	0.6	0.6	0.6	0.6

Bearing type	: 6314 C3	Non drive end	6314 C3	Foundation loads	
Sealing	: Taconite		Taconite	Max. traction	: 497 kgf
	: Labyrinth		Labyrinth	Max. compression	: 497 kgf
Lubrication interval	: 4000 h		4000 h		
Lubricant amount	: 27 g		27 g		
Lubricant type	: Mobil Polyrex EM				

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	22/10/2024		1 / 9	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 9	
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943424



Performance : 460 V 60 Hz 2P

Rated current : 81.9 A
LRC : 6.6
Rated torque : 15.3 kgfm
Locked rotor torque : 220 %
Breakdown torque : 270 %
Rated speed : 3550 rpm

Moment of inertia (J) : 0.5023 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 3 / 9Revision		
Checked by				
Date	22/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943424



Performance : 380 V 50 Hz 2P IE3

Rated current : 66.7 A
LRC : 7.8
Rated torque : 12.3 kgfm
Locked rotor torque : 240 %
Breakdown torque : 320 %
Rated speed : 2960 rpm

Moment of inertia (J) : 0.5023 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				4 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943424



Performance : 400 V 50 Hz 2P IE3

Rated current : 64.8 A
LRC : 8.5
Rated torque : 12.2 kgfm
Locked rotor torque : 260 %
Breakdown torque : 350 %
Rated speed : 2965 rpm

Moment of inertia (J) : 0.5023 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	22/10/2024			

Page 5 / 9
Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943424



Performance : 415 V 50 Hz 2P IE3

Rated current : 62.4 A
LRC : 9.1
Rated torque : 12.2 kgfm
Locked rotor torque : 290 %
Breakdown torque : 380 %
Rated speed : 2970 rpm

Moment of inertia (J) : 0.5023 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				6 / 9	
Date					

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943424



Performance : 380 V 50 Hz 2P IE1

Rated current : 100 A
LRC : 5.2
Rated torque : 18.6 kgfm
Locked rotor torque : 160 %
Breakdown torque : 200 %
Rated speed : 2930 rpm

Moment of inertia (J) : 0.5023 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 7 / 9Revision		
Checked by				
Date	22/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943424



Performance : 400 V 50 Hz 2P IE1

Rated current : 94.8 A
LRC : 5.8
Rated torque : 18.5 kgfm
Locked rotor torque : 175 %
Breakdown torque : 220 %
Rated speed : 2940 rpm

Moment of inertia (J) : 0.5023 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 8 / 9Revision	
Checked by					
Date	22/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943424




Performance : 415 V 50 Hz 2P IE1

Rated current : 91.4 A
LRC : 6.2
Rated torque : 18.5 kgfm
Locked rotor torque : 190 %
Breakdown torque : 240 %
Rated speed : 2950 rpm

Moment of inertia (J) : 0.5023 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 9 / 9	Revision
Checked by					
Date	22/10/2024				



Without vertical jackscrews	
Sealing - Taconite labyrinth	
Grease outlet according to IEEE841	
Color RAL 5009	
Painting plan 222E	
Mounting B3R(D)	