

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11943491

Frame	: 444/5T	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: F-1
Duty cycle	: Cont.(S1)	Rotation ¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight ³	: 0.0 kg
Protection degree	: IP55	Moment of inertia (J)	: 3.10 kgm ²
Design	: B		

Output [HP]	75	60	60	60	75	75	75
Poles	8	8	8	8	8	8	8
Frequency [Hz]	60	50	50	50	50	50	50
Rated voltage [V]	460	380	400	415	380	400	415
Rated current [A]	93.4	95.5	95.8	94.9	114	109	106
L. R. Amperes [A]	598	525	565	607	536	567	604
LRC [A]	6.4x(Code H)	5.5x(Code G)	5.9x(Code H)	6.4x(Code J)	4.7x(Code E)	5.2x(Code F)	5.7x(Code G)
No load current [A]	40.0	39.3	43.6	47.0	39.3	43.6	47.0
Rated speed [RPM]	890	740	740	740	735	735	740
Slip [%]	1.11	1.33	1.33	1.33	2.00	2.00	1.33
Rated torque [kgfm]	61.2	58.8	58.8	58.8	74.1	74.1	73.6
Locked rotor torque [%]	170	170	200	220	140	160	180
Breakdown torque [%]	200	210	229	250	170	190	210
Service factor	1.25	1.00	1.00	1.00	1.00	1.00	1.00
Temperature rise	80 K	80 K	80 K	80 K	105 K	105 K	105 K
Locked rotor time	32s (cold) 18s (hot)	72s (cold) 40s (hot)	64s (cold) 36s (hot)	61s (cold) 34s (hot)	46s (cold) 26s (hot)	46s (cold) 26s (hot)	48s (cold) 27s (hot)
Noise level ²	63.0 dB(A)	59.0 dB(A)	59.0 dB(A)	59.0 dB(A)	59.0 dB(A)	59.0 dB(A)	59.0 dB(A)
Efficiency (%)	25%						
	50%	93.0	92.6	91.3	91.2	91.5	92.0
	75%	93.6	93.0	92.6	92.5	91.7	92.4
	100%	93.6	93.0	92.9	92.9	91.7	92.4
Power Factor	25%						
	50%	0.64	0.56	0.52	0.49	0.70	0.63
	75%	0.74	0.69	0.65	0.62	0.77	0.73
	100%	0.79	0.77	0.73	0.71	0.80	0.78

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	6.6	6.6	6.6	6.6	6.6	6.6
	P2 (0,5;1,0)	5.2	5.2	5.2	5.2	5.2	5.2
	P3 (0,25;1,0)	4.7	4.7	4.7	4.7	4.7	4.7
	P4 (0,9;0,5)	3.3	3.3	3.3	3.3	3.3	3.3
	P5 (0,5;0,5)	2.2	2.2	2.2	2.2	2.2	2.2
	P6 (0,5;0,25)	1.5	1.5	1.5	1.5	1.5	1.5
	P7 (0,25;0,25)	1.0	1.0	1.0	1.0	1.0	1.0

Bearing type	: 6319 C3	Non drive end	6316 C3	Foundation loads	
Sealing	: Taconite		Taconite	Max. traction	: 1351 kgf
	: Labyrinth		Labyrinth	Max. compression	: 1351 kgf
Lubrication interval	: 17000 h		20000 h		
Lubricant amount	: 45 g		34 g		
Lubricant type	: Mobil Polyrex EM				

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	23/10/2024		1 / 9	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 9		Revision
Checked by					
Date	23/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943491



Performance : 460 V 60 Hz 8P

Rated current : 93.4 A
LRC : 6.4
Rated torque : 61.2 kgfm
Locked rotor torque : 170 %
Breakdown torque : 200 %
Rated speed : 890 rpm

Moment of inertia (J) : 3.10 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.25
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	23/10/2024			

Page
3 / 9

Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11943491

LOAD PERFORMANCE CURVE



Performance : 380 V 50 Hz 8P IE3

Rated current	: 95.5 A	Moment of inertia (J)	: 3.10 kgm ²
LRC	: 5.5	Duty cycle	: Cont.(S1)
Rated torque	: 58.8 kgfm	Insulation class	: F
Locked rotor torque	: 170 %	Service factor	: 1.00
Breakdown torque	: 210 %	Temperature rise	: 80 K
Rated speed	: 740 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by		Page 4 / 9Revision			
Checked by					
Date	23/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943491



Performance : 400 V 50 Hz 8P IE3

Rated current : 95.8 A
LRC : 5.9
Rated torque : 58.8 kgfm
Locked rotor torque : 200 %
Breakdown torque : 229 %
Rated speed : 740 rpm

Moment of inertia (J) : 3.10 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 80 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 5 / 9Revision		
Checked by				
Date	23/10/2024			

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11943491

LOAD PERFORMANCE CURVE



Performance : 415 V 50 Hz 8P IE3

Rated current	: 94.9 A	Moment of inertia (J)	: 3.10 kgm ²
LRC	: 6.4	Duty cycle	: Cont.(S1)
Rated torque	: 58.8 kgfm	Insulation class	: F
Locked rotor torque	: 220 %	Service factor	: 1.00
Breakdown torque	: 250 %	Temperature rise	: 80 K
Rated speed	: 740 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by					
Date	23/10/2024				
			Page	Revision	
			6 / 9		

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943491



Performance : 380 V 50 Hz 8P IE2

Rated current : 114 A
LRC : 4.7
Rated torque : 74.1 kgfm
Locked rotor torque : 140 %
Breakdown torque : 170 %
Rated speed : 735 rpm

Moment of inertia (J) : 3.10 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	23/10/2024			

Page 7 / 9
Revision

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium Efficiency Three-Phase Product code : 11943491

LOAD PERFORMANCE CURVE



Performance : 400 V 50 Hz 8P IE2			
Rated current	: 109 A	Moment of inertia (J)	: 3.10 kgm ²
LRC	: 5.2	Duty cycle	: Cont.(S1)
Rated torque	: 74.1 kgfm	Insulation class	: F
Locked rotor torque	: 160 %	Service factor	: 1.00
Breakdown torque	: 190 %	Temperature rise	: 105 K
Rated speed	: 735 rpm	Design	: B

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 8 / 9	Revision
Checked by					
Date	23/10/2024				

LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IEEE 841 NEMA Premium
Efficiency Three-Phase

Product code : 11943491





Performance : 415 V 50 Hz 8P IE2

Rated current : 106 A
LRC : 5.7
Rated torque : 73.6 kgfm
Locked rotor torque : 180 %
Breakdown torque : 210 %
Rated speed : 740 rpm

Moment of inertia (J) : 3.10 kgm²
Duty cycle : Cont.(S1)
Insulation class : F
Service factor : 1.00
Temperature rise : 105 K
Design : B

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 9 / 9Revision		
Checked by				
Date	23/10/2024			



75 HP 08 Poles 60 Hz										A
					HYBRISUSER					
ECM		LOC		SUMMARY OF MODIFICATIONS			EXECUTED		CHECKED	
							RELEASED		DATE	
EXECUTED		HYBRISUSER		 THREE PH. MOTOR IEEE 841 W22 NEMA PREM. EFF. FRAME 444/5T IP55 TEFC			PREVIEW WDD 00			
CHECKED										
RELEASED										
REL. DATE										
							SHEET		/	