

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Tru-Metric IE3 Three-Phase Product code : 14330819

Frame	: 100L	Locked rotor time	: 27s (cold) 15s (hot)
Output	: 5 HP (3.7 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 4.88 A	Protection degree	: IP55
L. R. Amperes	: 42.5 A	Cooling method	: IC411 - TEFC
LRC	: 8.7	Mounting	: B35L(E)
No load current	: 1.74 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 3505 rpm	Noise level <sup>2</sup>	: 71.0 dB(A)
Slip	: 2.64 %	Starting method	: Direct On Line
Rated torque	: 1.04 kgfm	Approx. weight <sup>3</sup>	: 35.0 kg
Locked rotor torque	: 310 %		
Breakdown torque	: 380 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.0064 kgm <sup>2</sup>		
Design	: N		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	0.000	86.4	88.3	88.5	Max. traction	: 80 kgf
Power Factor	0.00	0.69	0.80	0.86	Max. compression	: 115 kgf

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
12.4	9.9	9.1	6.4	4.0	2.6	1.7

	Drive end	Non drive end
Bearing type	: 6206 ZZ	6205 ZZ
Sealing	: V'Ring	V'Ring
Lubrication interval	: 0 h	0 h
Lubricant amount	: 0 g	0 g
Lubricant type	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	24/10/2024			

Page 1 / 2  
Revision

# LOAD PERFORMANCE CURVE


Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Tru-Metric IE3 Three-Phase      Product code : 14330819

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 2P

Rated current	: 4.88 A	Moment of inertia (J)	: 0.0064 kgm <sup>2</sup>
LRC	: 8.7	Duty cycle	: S1
Rated torque	: 1.04 kgfm	Insulation class	: F
Locked rotor torque	: 310 %	Service factor	: 1.25
Breakdown torque	: 380 %	Temperature rise	: 80 K
Rated speed	: 3505 rpm	Design	: N

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 2 / 2Revision		
Checked by				
Date	24/10/2024			

