

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line		: Saw Arbor Motor Standard Efficiency Three-Phase		Product code : 10796958		
Frame	: 80M/MS	Locked rotor time	: 12s (cold) 7s (hot)			
Output	: 5 HP (3.7 kW)	Temperature rise	: 80 K			
Poles	: 2	Duty cycle	: S1			
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C			
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.			
Rated current	: 5.32 A	Protection degree	: IP54			
L. R. Amperes	: 42.5 A	Cooling method	: IC411 - TEFC			
LRC	: 8.0	Mounting	: B3R(D)			
No load current	: 2.30 A	Rotation ¹	: CCW			
Rated speed	: 3470 rpm	Noise level ²	: 62.0 dB(A)			
Slip	: 3.61 %	Starting method	: Direct On Line			
Rated torque	: 1.05 kgfm	Approx. weight ³	: 45.0 kg			
Locked rotor torque	: 340 %					
Breakdown torque	: 409 %					
Insulation class	: F					
Service factor	: 1.15					
Moment of inertia (J)	: 0.0041 kgm ²					
Design	: N					
Output	50%	75%	100%	Foundation loads		
Efficiency (%)	82.0	84.5	85.0	Max. traction : 67 kgf		
Power Factor	0.66	0.77	0.82	Max. compression : 112 kgf		
		<u>Drive end</u>		<u>Non drive end</u>		
Bearing type	:	6307 ZZ		6207 ZZ		
Sealing	:	Without Bearing Seal		Without Bearing Seal		
Lubrication interval	:	-		-		
Lubricant amount	:	-		-		
Lubricant type	:	Mobil Polyrex EM				
Notes						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	26/10/2024				1 / 2	

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage




Customer :

Product line : Saw Arbor Motor Standard
Efficiency Three-Phase

Product code : 10796958

LOAD PERFORMANCE CURVE



Performance : 575 V 60 Hz 2P

Rated current : 5.32 A
LRC : 8.0
Rated torque : 1.05 kgfm
Locked rotor torque : 340 %
Breakdown torque : 409 %
Rated speed : 3470 rpm




Moment of inertia (J) : 0.0041 kgm²
Duty cycle : S1
Insulation class : F
Service factor : 1.15
Temperature rise : 80 K
Design : N

Rev.	Changes Summary	Performed	Checked	Date
Performed by			Page	Revision
Checked by				
Date				

EIXO/SHAFT	
PADRÃO/STANDARD	
OPCIONAL/OPTIONAL	
ESPECIAL/SPECIAL	x

Dimensões em mm
Dimensions in mm

THIS IS AN UPDATED REVISION, THE PREVIOUS ONE MUST BE DISREGARDED.



A
B
C
D
E

CÓPIA SEM CONTROLE
LIBERADO
ZME A3

X2045.02.03 MEC

Fornecido com 2 arruelas onduladas no mancal traseiro para eliminal a folga axial Supplied with 2 washer on N.D.E. bearing to eliminate the axial clearance						
Sentido de Rotação Anti-Horário / Counter clockwise rotation						
Isolamento classe F (Dt=80K) / Class F insulation - 80K temperature rise						
Fator de Serviço 1.00 / Service factor 1.0						
Forma Construtiva B3D / Mounting - B3R(D)						
500001273532		ALT. CONFORME CLAIM 414559447	FRANCINES	CASSIO	23.02.2017	03
500001273890			FRANCINES	GEVERSON	13.02.2017	
ECM ECM	LOC LOC	RESUMO MODIFICAÇÃO SUMMARY OF MODIFICATIONS	EXECUTADO EXECUTED	VERIFICADO CHECKED	LIBERADO RELEASED	DATA DATE
EXEC. /EXECUTED	RUDIK	V.J.PAMENSKY CA (ME 80M/MS)				
VERIF. /CHECKED						
LIBER. /RELEASED	RUDMAR					
DATA LB /REL DT	21.09.2008	JARAGUÁ DO SUL	ENGENHARIA DE PRODUTO	FOLHA/SHEET	01 / 01	
			E1003281			
			000 03			
					WEG	