

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : General Single-Phase Product code : 10796011

Frame	: G56H	Locked rotor time	: 10s (cold) 6s (hot)
Output	: 1 HP (0.75 kW)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 115/208-230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 11.0/5.80-5.50 A	Protection degree	: IP55
L. R. Amperes	: 66.0/34.8-33.0 A	Cooling method	: IC411 - TEFC
LRC	: 6.0x(Code J)	Mounting	: F-1
No load current	: 6.60/2.85-3.30 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1150 rpm	Noise level ²	: 50.0 dB(A)
Slip	: 4.17 %	Starting method	: Direct On Line
Rated torque	: 0.631 kgfm	Approx. weight ³	: 22.7 kg
Locked rotor torque	: 240 %		
Breakdown torque	: 220 %		
Insulation class	: B		
Service factor	: 1.15		
Moment of inertia (J)	: 0.0090 kgm ²		

Output	50%	75%	100%	Foundation loads	
Efficiency (%)	64.0	69.0	73.0	Max. traction	: 33 kgf
Power Factor	0.63	0.72	0.80	Max. compression	: 56 kgf

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6204 ZZ	6203 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2		
Checked by				
Date	26/10/2024			
			Revision	

LOAD PERFORMANCE CURVE

Single Phase Induction Motor - Squirrel Cage




Customer :

Product line : General Single-Phase

Product code : 10796011

LOAD PERFORMANCE CURVE



Performance : 115/208-230 V 60 Hz 6P

Rated current : 11.0/5.80-5.50 A
LRC : 6.0
Rated torque : 0.631 kgfm
Locked rotor torque : 240 %
Breakdown torque : 220 %
Rated speed : 1150 rpm

Moment of inertia (J) : 0.0090 kgm²
Duty cycle : Cont.(S1)
Insulation class : B
Service factor :
Temperature rise : 80 K

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date					

