

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : General High Efficiency Three-Phase Product code : 11993753

|                       |                           |                             |                        |
|-----------------------|---------------------------|-----------------------------|------------------------|
| Frame                 | : E143/5TC                | Locked rotor time           | : 27s (cold) 15s (hot) |
| Output                | : 1 HP (0.75 kW)          | Temperature rise            | : 80 K                 |
| Poles                 | : 4                       | Duty cycle                  | : Cont.(S1)            |
| Frequency             | : 60 Hz                   | Ambient temperature         | : -20°C to +40°C       |
| Rated voltage         | : 230/460 V               | Altitude                    | : 1000 m.a.s.l.        |
| Rated current         | : 3.00/1.50 A             | Protection degree           | : IP21                 |
| L. R. Amperes         | : 23.4/11.7 A             | Cooling method              | : IC01 - ODP           |
| LRC                   | : 7.8x(Code L)            | Mounting                    | : F-1                  |
| No load current       | : 2.00/1.00 A             | Rotation <sup>1</sup>       | : Both (CW and CCW)    |
| Rated speed           | : 1740 rpm                | Noise level <sup>2</sup>    | : 50.0 dB(A)           |
| Slip                  | : 3.33 %                  | Starting method             | : Direct On Line       |
| Rated torque          | : 0.417 kgfm              | Approx. weight <sup>3</sup> | : 0.0 kg               |
| Locked rotor torque   | : 310 %                   |                             |                        |
| Breakdown torque      | : 350 %                   |                             |                        |
| Insulation class      | : F                       |                             |                        |
| Service factor        | : 1.15                    |                             |                        |
| Moment of inertia (J) | : 0.0053 kgm <sup>2</sup> |                             |                        |
| Design                | : B                       |                             |                        |

|                |      |      |      |                  |          |
|----------------|------|------|------|------------------|----------|
| Output         | 50%  | 75%  | 100% | Foundation loads |          |
| Efficiency (%) | 80.0 | 81.5 | 82.5 | Max. traction    | : 41 kgf |
| Power Factor   | 0.57 | 0.68 | 0.76 | Max. compression | : 41 kgf |

|                      | Drive end              | Non drive end          |
|----------------------|------------------------|------------------------|
| Bearing type         | : 6205 ZZ              | : 6204 ZZ              |
| Sealing              | : Without Bearing Seal | : Without Bearing Seal |
| Lubrication interval | : -                    | : -                    |
| Lubricant amount     | : -                    | : -                    |
| Lubricant type       | : Mobil Polyrex EM     |                        |

Notes  
USABLE @208V 3.30A SF 1.00 SFA 3.30A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev.         | Changes Summary | Performed | Checked | Date |
|--------------|-----------------|-----------|---------|------|
|              |                 |           |         |      |
| Performed by |                 |           |         |      |
| Checked by   |                 |           |         |      |
| Date         | 24/08/2025      |           |         |      |

Page 1 / 2  
Revision

# LOAD PERFORMANCE CURVE


## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : General High Efficiency Three-Phase

Product code : 11993753




Performance : 230/460 V 60 Hz 4P

Rated current : 3.00/1.50 A  
LRC : 7.8  
Rated torque : 0.417 kgfm  
Locked rotor torque : 310 %  
Breakdown torque : 350 %  
Rated speed : 1740 rpm

Moment of inertia (J) : 0.0053 kgm<sup>2</sup>  
Duty cycle : Cont.(S1)  
Insulation class : F  
Service factor :  
Temperature rise : 80 K  
Design : B

| Rev.         | Changes Summary |  | Performed | Checked       | Date     |
|--------------|-----------------|--|-----------|---------------|----------|
|              |                 |  |           |               |          |
| Performed by |                 |  |           | Page<br>2 / 2 | Revision |
| Checked by   |                 |  |           |               |          |
| Date         | 24/08/2025      |  |           |               |          |



WEG's property. Forbidden reproduction without previous authorization.